



Open CASCADE Technology
7.3.0

Boolean Operations

May 26, 2018

Contents

1	Introduction	7
2	Overview	8
2.1	Operators	8
2.1.1	Boolean operator	8
2.1.2	General Fuse operator	8
2.1.3	Splitter operator	9
2.1.4	Section operator	10
2.2	Parts of algorithms	10
3	Terms and Definitions	11
3.1	Interferences	11
3.1.1	Vertex/Vertex interference	11
3.1.2	Vertex/Edge interference	12
3.1.3	Vertex/Face interference	12
3.1.4	Edge/Edge interference	13
3.1.5	Edge/Face interference	14
3.1.6	Face/Face Interference	16
3.1.7	Vertex/Solid Interference	18
3.1.8	Edge/Soild Interference	18
3.1.9	Face/Soild Interference	19
3.1.10	Solid/Soild Interference	19
3.1.11	Computation Order	19
3.1.12	Results	20
3.2	Paves	20
3.3	Pave Blocks	21
3.4	Shrunk Range	21
3.5	Common Blocks	22
3.6	FacelInfo	23
4	Data Structure	25
4.1	Arguments	25
4.2	Shapes	26
4.3	Interferences	26
4.4	Pave, PaveBlock and CommonBlock	27
4.5	Points and Curves	28
4.6	FacelInfo	28
5	Root Classes	29
5.1	Class BOPAlgo_Options	29

5.2	Class BOPAlgo_Algo	29
6	Intersection Part	30
6.1	Initialization	30
6.2	Compute Vertex/Vertex Interferences	31
6.3	Compute Vertex/Edge Interferences	31
6.4	Update Pave Blocks	32
6.5	Compute Edge/Edge Interferences	32
6.6	Compute Vertex/Face Interferences	33
6.7	Compute Edge/Face Interferences	33
6.8	Build Split Edges	34
6.9	Compute Face/Face Interferences	35
6.10	Build Section Edges	35
6.11	Build P-Curves	36
6.12	Process Degenerated Edges	36
7	General description of the Building Part	37
8	General Fuse Algorithm	38
8.1	Arguments	38
8.2	Results	38
8.3	Options	38
8.4	Usage	39
8.5	Examples	40
8.5.1	Case 1: Three edges intersecting at a point	40
8.5.2	Case 2: Two wires and an edge	40
8.5.3	Case 3: An edge intersecting with a face	41
8.5.4	Case 4: An edge lying on a face	42
8.5.5	Case 5: An edge and a shell	42
8.5.6	Case 6: A wire and a shell	43
8.5.7	Case 7: Three faces	43
8.5.8	Case 8: A face and a shell	44
8.5.9	Case 9: A shell and a solid	44
8.5.10	Case 10: A compound and a solid	45
8.6	Class BOPAlgo_Builder	46
8.6.1	Fields	46
8.6.2	Initialization	47
8.6.3	Build Images for Vertices	47
8.6.4	Build Result of Type Vertex	47
8.6.5	Build Images for Edges	47
8.6.6	Build Result of Type Edge	47

8.6.7	Build Images for Wires	47
8.6.8	Build Result of Type Wire	48
8.6.9	Build Images for Faces	48
8.6.10	Build Result of Type Face	49
8.6.11	Build Images for Shells	49
8.6.12	Build Result of Type Shell	49
8.6.13	Build Images for Solids	49
8.6.14	Build Result of Type Solid	50
8.6.15	Build Images for Type CompSolid	50
8.6.16	Build Result of Type Compsolid	50
8.6.17	Build Images for Compounds	50
8.6.18	Build Result of Type Compound	50
8.6.19	Post-Processing	50
9	Splitter Algorithm	51
9.1	Arguments	51
9.2	Results	51
9.3	Usage	51
9.3.1	API	51
9.3.2	DRAW	51
9.4	Examples	52
9.4.1	Example 1	52
9.4.2	Example 2	52
9.4.3	Example 3	53
10	Boolean Operations Algorithm	54
10.1	Arguments	54
10.2	Results. General Rules	54
10.3	Examples	55
10.3.1	Case 1: Two Vertices	55
10.3.2	Case 2: A Vertex and an Edge	56
10.3.3	Case 3: A Vertex and a Face	57
10.3.4	Case 4: A Vertex and a Solid	57
10.3.5	Case 5: Two edges intersecting at one point	58
10.3.6	Case 6: Two edges having a common block	60
10.3.7	Case 7: An Edge and a Face intersecting at a point	62
10.3.8	Case 8: A Face and an Edge that have a common block	63
10.3.9	Case 9: An Edge and a Solid intersecting at a point	64
10.3.10	Case 10: An Edge and a Solid that have a common block	66
10.3.11	Case 11: Two intersecting faces	67
10.3.12	Case 12: Two faces that have a common part	69

10.3.13 Case 13: Two faces that have a common edge	70
10.3.14 Case 14: Two faces that have a common vertex	72
10.3.15 Case 15: A Face and a Solid that have an intersection curve.	73
10.3.16 Case 16: A Face and a Solid that have overlapping faces.	74
10.3.17 Case 17: A Face and a Solid that have overlapping edges.	76
10.3.18 Case 18: A Face and a Solid that have overlapping vertices.	77
10.3.19 Case 19: Two intersecting Solids.	78
10.3.20 Case 20: Two Solids that have overlapping faces.	80
10.3.21 Case 21: Two Solids that have overlapping edges.	82
10.3.22 Case 22: Two Solids that have overlapping vertices.	83
10.3.23 Case 23: A Shell and a Wire cut by a Solid.	85
10.3.24 Case 24: Two Wires that have overlapping edges.	86
10.4 Class BOPAlgo_BOP	89
10.5 Building Draft Result	89
10.6 Building the Result	89
11 Section Algorithm	91
11.1 Arguments	91
11.2 Results and general rules	91
11.3 Examples	91
11.3.1 Case 1: Two Vertices	91
11.3.2 Case 1: Case 2: A Vertex and an Edge	92
11.3.3 Case 1: Case 2: A Vertex and a Face	92
11.3.4 Case 4: A Vertex and a Solid	93
11.3.5 Case 5: Two edges intersecting at one point	93
11.3.6 Case 6: Two edges having a common block	94
11.3.7 Case 7: An Edge and a Face intersecting at a point	94
11.3.8 Case 8: A Face and an Edge that have a common block	95
11.3.9 Case 9: An Edge and a Solid intersecting at a point	96
11.3.10 Case 10: An Edge and a Solid that have a common block	96
11.3.11 Case 11: Two intersecting faces	97
11.3.12 Case 12: Two faces that have a common part	98
11.3.13 Case 13: Two faces that have overlapping edges	98
11.3.14 Case 14: Two faces that have overlapping vertices	99
11.3.15 Case 15: A Face and a Solid that have an intersection curve	100
11.3.16 Case 16: A Face and a Solid that have overlapping faces.	100
11.3.17 Case 17: A Face and a Solid that have overlapping edges.	101
11.3.18 Case 18: A Face and a Solid that have overlapping vertices.	102
11.3.19 Case 19: Two intersecting Solids	102
11.3.20 Case 20: Two Solids that have overlapping faces	103

11.3.21 Case 21: Two Solids that have overlapping edges	104
11.3.22 Case 22: Two Solids that have overlapping vertices	104
11.4 Class BOPAlgo_Section	105
11.5 Building the Result	105
12 Volume Maker Algorithm	107
12.1 Usage	107
12.2 Examples	107
13 Cells Builder algorithm	109
13.1 Usage	109
13.2 Examples	110
14 Algorithm Limitations	117
14.1 Arguments	117
14.1.1 Common requirements	117
14.1.2 Pure self-interference	117
14.1.3 Self-interferences due to tolerances	120
14.1.4 Parametric representation	122
14.1.5 Using tolerances of vertices to fix gaps	124
14.2 Intersection problems	125
14.2.1 Pure intersections and common zones	125
14.2.2 Tolerances and inaccuracies	126
14.2.3 Acquired Self-interferences	128
15 Advanced Options	130
15.1 Fuzzy Boolean Operation	130
15.1.1 Examples	130
15.2 Gluing Operation	136
15.2.1 Usage	138
15.2.2 Examples	139
15.3 Safe processing mode	140
15.3.1 Usage	140
15.4 How to disable check of input solids for inverted status	140
15.4.1 Usage	140
15.5 Usage of Oriented Bounding Boxes	141
15.5.1 Usage	141
16 Errors and warnings reporting system	142
17 History Information	143
17.1 Examples	143

17.1.1 Deleted shapes	143
17.1.2 Modified shapes	143
17.1.3 Generated shapes	144
18 Usage	145
18.1 Package BRepAlgoAPI	145
18.2 Package BOPTest	146
18.2.1 Case 1. General Fuse operation	146
18.2.2 Case 2. Splitting operation	146
18.2.3 Case 3. Common operation	147
18.2.4 Case 4. Fuse operation	148
18.2.5 Case 5. Cut operation	149
18.2.6 Case 6. Section operation	150

1 Introduction

This document provides a comprehensive description of the Boolean Operation Algorithm (BOA) as it is implemented in Open CASCADE Technology. The Boolean Component contains:

- General Fuse Operator (GFA),
- Boolean Operator (BOA),
- Section Operator (SA),
- Splitter Operator (SPA).

GFA is the base algorithm for BOA, SPA, SA.

GFA has a history-based architecture designed to allow using OCAF naming functionality. The architecture of GFA is expandable, that allows creating new algorithms basing on it.

2 Overview

2.1 Operators

2.1.1 Boolean operator

The Boolean operator provides the operations (Common, Fuse, Cut) between two groups: *Objects* and *Tools*. Each group consists of an arbitrary number of arguments in terms of *TopoDS_Shape*.

The operator can be represented as:

$$R_B = B_j (G_1, G_2),$$

where:

- R_B – result of the operation;
- B_j – operation of type j (Common, Fuse, Cut);
- $G_1 = \{S_{11}, S_{12} \dots S_{1n1}\}$ group of arguments (Objects);
- $G_2 = \{S_{21}, S_{22} \dots S_{2n2}\}$ group of arguments (Tools);
- n_1 – Number of arguments in *Objects* group;
- n_2 – Number of arguments in *Tools* group.

Note There is an operation *Cut21*, which is an extension for forward Cut operation, i.e $Cut21 = Cut(G2, G1)$.

For more details see [Boolean Operations Algorithm](#) section.

2.1.2 General Fuse operator

The General fuse operator can be applied to an arbitrary number of arguments in terms of *TopoDS_Shape*.

The GFA operator can be represented as:

$$R_{GF} = GF (S_1, S_2 \dots S_n),$$

where

- R_{GF} – result of the operation,
- $S_1, S_2 \dots S_n$ – arguments of the operation,
- n – number of arguments.

The result of the Boolean operator, R_B , can be obtained from R_{GF} .

For example, for two arguments S_1 and S_2 the result R_{GF} is

$$R_{GF} = GF (S_1, S_2) = S_{p1} + S_{p2} + S_{p12}$$




Figure 1: Operators

This Figure shows that

- $B_{common}(S_1, S_2) = S_{p12}$;
- $B_{cut12}(S_1, S_2) = S_{p1}$;
- $B_{cut21}(S_1, S_2) = S_{p2}$;
- $B_{fuse}(S_1, S_2) = S_{p1} + S_{p2} + S_{p12}$

$$R_{GF} = GF(S_1, S_2) = B_{fuse} = B_{common} + B_{cut12} + B_{cut21}.$$

The fact that R_{GF} contains the components of R_B allows considering GFA as the general case of BOA. So it is possible to implement BOA as a subclass of GFA.

For more details see [General Fuse Algorithm](#) section.

2.1.3 Splitter operator

The Splitter operator can be applied to an arbitrary number of arguments in terms of *TopoDS_Shape*. The arguments are divided into two groups: *Objects* and *Tools*. The result of *SPA* contains all parts that belong to the *Objects* but does not contain the parts that belong to the *Tools*.

The *SPA* operator can be represented as follows:

$R_{SPA} = SPA(G_1, G_2)$, where:

- R_{SPA} – is the result of the operation;
- $G_1 = \{S_{11}, S_{12} \dots S_{1n1}\}$ group of arguments (*Objects*);
- $G_2 = \{S_{21}, S_{22} \dots S_{2n2}\}$ group of arguments (*Tools*);
- n_1 – Number of arguments in *Objects* group;
- n_2 – Number of arguments in *Tools* group.

The result R_{SPA} can be obtained from R_{GF} .

For example, for two arguments S_1 and S_2 the result R_{SPA} is

$$R_{SPA} = SPA(S_1, S_2) = S_{p1} + S_{p12}.$$

In case when all arguments of the *SPA* are *Objects* and there are no *Tools*, the result of *SPA* is equivalent to the result of *GFA*.

For example, when G_1 consists of shapes S_1 and S_2 the result of *SPA* is

$$R_{SPA}=SPA(S_1, S_2) = S_{p1} + S_{p2} + S_{p12} = GF(S_1, S_2)$$

The fact that the R_{GF} contains the components of R_{SPA} allows considering GFA as the general case of SPA . Thus, it is possible to implement SPA as a subclass of GFA .

For more details see [Splitter Algorithm](#) section.

2.1.4 Section operator

The Section operator SA can be applied to arbitrary number of arguments in terms of $TopoDS_Shape$. The result of SA contains vertices and edges in accordance with interferences between the arguments. The SA operator can be represented as follows: $R_{SA}=SA(S1, S2... Sn)$, where

- R_{SA} – the operation result;
- $S1, S2 ... Sn$ – the operation arguments;
- n – the number of arguments.

For more details see [Section Algorithm](#) section.

2.2 Parts of algorithms

GFA, BOA, SPA and SA have the same Data Structure (DS). The main goal of the Data Structure is to store all necessary information for input data and intermediate results.

The operators consist of two main parts:

- Intersection Part (IP). The main goal of IP is to compute the interferences between sub-shapes of arguments. The IP uses DS to retrieve input data and store the results of intersections.
- Building Part (BP). The main goal of BP is to build required result of an operation. This part also uses DS to retrieve data and store the results.

As it follows from the definition of operator results, the main differences between GFA, BOA, SPA and SA are in the Building Part. The Intersection Part is the same for the algorithms.

3 Terms and Definitions

This chapter provides the background terms and definitions that are necessary to understand how the algorithms work.

3.1 Interferences

There are two groups of interferences.

At first, each shape having a boundary representation (vertex, edge, face) has an internal value of geometrical tolerance. The shapes interfere with each other in terms of their tolerances. The shapes that have a boundary representation interfere when there is a part of 3D space where the distance between the underlying geometry of shapes is less or equal to the sum of tolerances of the shapes. Three types of shapes: vertex, edge and face – produce six types of **BRep interferences**:

- Vertex/Vertex,
- Vertex/Edge,
- Vertex/Face,
- Edge/Edge,
- Edge/Face and
- Face/Face.

At second, there are interferences that occur between a solid $Z1$ and a shape $S2$ when $Z1$ and $S2$ have no BRep interferences but $S2$ is completely inside of $Z1$. These interferences are **Non-BRep interferences**. There are four possible cases:

- Vertex/Solid,
- Edge/Solid,
- Face/Solid and
- Solid/Solid.

3.1.1 Vertex/Vertex interference

For two vertices V_i and V_j , the distance between their corresponding 3D points is less than the sum of their tolerances $Tol(V_i)$ and $Tol(V_j)$.




Figure 2: Vertex/vertex interference

The result is a new vertex V_n with 3D point P_n and tolerance value $Tol(V_n)$.

The coordinates of P_n and the value $Tol(V_n)$ are computed as the center and the radius of the sphere enclosing the tolerance spheres of the source vertices (V_1, V_2).

3.1.2 Vertex/Edge interference

For a vertex V_i and an edge E_j , the distance D between 3D point of the vertex and its projection on the 3D curve of edge E_j is less or equal than sum of tolerances of vertex $Tol(V_i)$ and edge $Tol(E_j)$.




Figure 3: Vertex/edge interference

The result is vertex V_i with the corresponding tolerance value $Tol(V_i) = \text{Max}(Tol(V_i), D + Tol(E_j))$, where $D = \text{distance}(P_i, PP_i)$;

and parameter t_i of the projected point PP_i on 3D curve C_j of edge E_j .

3.1.3 Vertex/Face interference

For a vertex V_i and a face F_j the distance D between 3D point of the vertex and its projection on the surface of the face is less or equal than sum of tolerances of the vertex $Tol(V_i)$ and the face $Tol(F_j)$.




Figure 4: Vertex/face interference

The result is vertex V_i with the corresponding tolerance value $Tol(V_i) = \text{Max}(Tol(V_i), D + Tol(F_j))$, where $D = \text{distance}(P_i, PP_i)$

and parameters u_i, v_i of the projected point PP_i on surface S_j of face F_j .

3.1.4 Edge/Edge interference

For two edges E_i and E_j (with the corresponding 3D curves C_i and C_j) there are some places where the distance between the curves is less than (or equal to) sum of tolerances of the edges.

Let us examine two cases:

In the first case two edges have one or several common parts of 3D curves in terms of tolerance.




Figure 5: Edge/edge interference: common parts

The results are:

- Parametric range $[t_{i1}, t_{i2}]$ for 3D curve C_i of edge E_i .
- Parametric range $[t_{j1}, t_{j2}]$ for 3D curve C_j of edge E_j .

In the second case two edges have one or several common points in terms of tolerance.




Figure 6: Edge/edge interference: common points

The result is a new vertex V_n with 3D point P_n and tolerance value $Tol(V_n)$.

The coordinates of P_n and the value $Tol(V_n)$ are computed as the center and the radius of the sphere enclosing the tolerance spheres of the corresponding nearest points P_i, P_j of 3D curves C_i, C_j of source edges E_i, E_j .

- Parameter t_i of P_i for the 3D curve C_i .
- Parameter t_j of P_j for the 3D curve C_j .

3.1.5 Edge/Face interference

For an edge E_i (with the corresponding 3D curve C_i) and a face F_j (with the corresponding 3D surface S_j) there are some places in 3D space, where the distance between C_i and surface S_j is less than (or equal to) the sum of tolerances of edge E_i and face F_j .

Let us examine two cases:

In the first case Edge E_i and Face F_j have one or several common parts in terms of tolerance.




Figure 7: Edge/face interference: common parts

The result is a parametric range $[t_1, t_2]$ for the 3D curve C_i of the edge E_i .

In the second case Edge E_i and Face F_j have one or several common points in terms of tolerance.




Figure 8: Edge/face interference: common points

The result is a new vertex V_n with 3D point P_n and tolerance value $Tol(V_n)$.

The coordinates of P_n and the value $Tol(V_n)$ are computed as the center and the radius of the sphere enclosing the tolerance spheres of the corresponding nearest points P_i , P_j of 3D curve C_i and surface S_j of source edges E_i , F_j .

- Parameter t_i of P_i for the 3D curve C_i .
- Parameters u_i and v_i of the projected point PP_i on the surface S_j of the face F_j .

3.1.6 Face/Face Interference

For a face F_i and a face F_j (with the corresponding surfaces S_i and S_j) there are some places in 3D space, where the distance between the surfaces is less than (or equal to) sum of tolerances of the faces.




Figure 9: Face/face interference: common curves

In the first case the result contains intersection curves C_{ijk} ($k = 0, 1, 2, \dots, k_N$, where k_N is the number of intersection curves with corresponding values of tolerances $Tol(C_{ijk})$).




Figure 10: Face/face interference: common points

In the second case Face F_i and face F_j have one or several new vertices V_{ijm} , where $m=0,1,2, \dots, mN$, mN is the number of intersection points.

The coordinates of a 3D point P_{ijm} and the value $Tol(V_{ijm})$ are computed as the center and the radius of the sphere enclosing the tolerance spheres of the corresponding nearest points P_i, P_j of the surface S_i, S_j of source shapes F_i, F_j .

- Parameters u_j, v_j belong to point PP_j projected on surface S_j of face F_j .

- Parameters u_i and v_i belong to point PP_i projected on surface Si of face Fi .

3.1.7 Vertex/Solid Interference

For a vertex V_i and a solid Z_j there is Vertex/Solid interference if the vertex V_i has no BRep interferences with any sub-shape of Z_j and V_i is completely inside the solid Z_j .




Figure 11: Vertex/Solid Interference

3.1.8 Edge/Solid Interference

For an edge E_i and a solid Z_j there is Edge/Solid interference if the edge E_i and its sub-shapes have no BRep interferences with any sub-shape of Z_j and E_i is completely inside the solid Z_j .




Figure 12: Edge/Solid Interference

3.1.9 Face/Solid Interference

For a face F_i and a solid Z_j there is Face/Solid interference if the face F_i and its sub-shapes have no BRep interferences with any sub-shape of Z_j and F_i is completely inside the solid Z_j .




Figure 13: Face/Solid Interference

3.1.10 Solid/Solid Interference

For a solid Z_i and a solid Z_j there is Solid/Solid interference if the solid Z_i and its sub-shapes have no BRep interferences with any sub-shape of Z_j and Z_i is completely inside the solid Z_j .




Figure 14: Solid/Solid Interference

3.1.11 Computation Order

The interferences between shapes are computed on the basis of increasing of the dimension value of the shape in the following order:

- Vertex/Vertex,
- Vertex/Edge,
- Edge/Edge,
- Vertex/Face,
- Edge/Face,
- Face/Face,
- Vertex/Solid,
- Edge/Solid,
- Face/Solid,
- Solid/Solid.

This order allows avoiding the computation of redundant interferences between upper-level shapes S_i and S_j when there are interferences between lower sub-shapes S_{ik} and S_{jm} .

3.1.12 Results

- The result of the interference is a shape that can be either interfered shape itself (or its part) or a new shape.
- The result of the interference is a shape with the dimension value that is less or equal to the minimal dimension value of interfered shapes. For example, the result of Vertex/Edge interference is a vertex, but not an edge.
- The result of the interference splits the source shapes on the parts each time as it can do that.

3.2 Paves

The result of interferences of the type Vertex/Edge, Edge/Edge and Edge/Face in most cases is a vertex (new or old) lying on an edge.

The result of interferences of the type Face/Face in most cases is intersection curves, which go through some vertices lying on the faces.

The position of vertex V_i on curve C can be defined by a value of parameter t_i of the 3D point of the vertex on the curve. Pave PV_i on curve C is a structure containing the vertex V_i and correspondent value of the parameter t_i of the 3D point of the vertex on the curve. Curve C can be a 3D or a 2D curve.




Figure 15: Paves

Two paves $PV1$ and $PV2$ on the same curve C can be compared using the parameter value

$$PV1 > PV2 \text{ if } t_1 > t_2$$

The usage of paves allows binding of the vertex to the curve (or any structure that contains a curve: edge, intersection curve).

3.3 Pave Blocks

A set of paves PVi ($i=1, 2 \dots nPV$), where nPV is the number of paves] of curve C can be sorted in the increasing order using the value of parameter t on curve C .

A pave block PBi is a part of the object (edge, intersection curve) between neighboring paves.




Figure 16: Pave Blocks

Any finite source edge E has at least one pave block that contains two paves PVb and PVe :

- Pave PVb corresponds to the vertex Vb with minimal parameter t_b on the curve of the edge.
- Pave PVe corresponds to the vertex Ve with maximal parameter t_e on the curve of the edge.

3.4 Shrunk Range

Pave block PV of curve C is bounded by vertices $V1$ and $V2$ with tolerance values $Tol(V1)$ and $Tol(V2)$. Curve C has its own tolerance value $Tol(C)$:

- In case of edge, the tolerance value is the tolerance of the edge.
- In case of intersection curve, the tolerance value is obtained from an intersection algorithm.




Figure 17: Shrunken Range

The theoretical parametric range of the pave block is $[t1C, t2C]$.

The positions of the vertices $V1$ and $V2$ of the pave block can be different. The positions are determined by the following conditions:

- Distance $(P1, P1c)$ is equal or less than $Tol(V1) + Tol(C)$
- Distance $(P2, P2c)$ is equal or less than $Tol(V2) + Tol(C)$

The Figure shows that each tolerance sphere of a vertex can reduce the parametric range of the pave block to a range $[t1S, t2S]$. The range $[t1S, t2S]$ is the shrunken range of the pave block.

The shrunken range of the pave block is the part of 3D curve that can interfere with other shapes.

3.5 Common Blocks

The interferences of the type Edge/Edge, Edge/Face produce results as common parts.

In case of Edge/Edge interference the common parts are pave blocks that have different base edges.




Figure 18: Common Blocks: Edge/Edge interference

If the pave blocks $PB_1, PB_2 \dots PB_{NbPB}$, where $NbPB$ is the number of pave blocks have the same bounding vertices and geometrically coincide, the pave blocks form common block CB .

In case of Edge/Face interference the common parts are pave blocks lying on a face(s).




Figure 19: Common Blocks: Edge/Face interference

If the pave blocks PBi geometrically coincide with a face Fj , the pave blocks form common block CB .

In general case a common block CB contains:

- Pave blocks PBi ($i=0, 1, 2, 3 \dots NbPB$).
- A set of faces Fj ($j=0, 1 \dots NbF$), NbF – number of faces.

3.6 FacelInfo

The structure *FacelInfo* contains the following information:

- Pave blocks that have state **In** for the face;
- Vertices that have state **In** for the face;
- Pave blocks that have state **On** for the face;
- Vertices that have state **On** for the face;
- Pave blocks built up from intersection curves for the face;
- Vertices built up from intersection points for the face.




Figure 20: Face Info

In the figure, for face $F1$:

- Pave blocks that have state **In** for the face: PB_{in1} .
- Vertices that have state **In** for the face: V_{in1} .
- Pave blocks that have state **On** for the face: PB_{on11} , PB_{on12} , PB_{on2} , PB_{on31} , PB_{on32} , PB_{on4} .
- Vertices that have state **On** for the face: $V1$, $V2$, $V3$, $V4$, $V5$, $V6$.
- Pave blocks built up from intersection curves for the face: PB_{sc1} .
- Vertices built up from intersection points for the face: none

4 Data Structure

Data Structure (DS) is used to:

- Store information about input data and intermediate results;
- Provide the access to the information;
- Provide the links between the chunks of information.

This information includes:

- Arguments;
- Shapes;
- Interferences;
- Pave Blocks;
- Common Blocks.

Data Structure is implemented in the class *BOPDS_DS*.

4.1 Arguments

The arguments are shapes (in terms of *TopoDS_Shape*):

- Number of arguments is unlimited.
- Each argument is a valid shape (in terms of *BRepCheck_Analyzer*).
- Each argument can be of one of the following types (see the Table):

No	Type	Index of Type
1	COMPOUND	0
2	COMPSOLID	1
3	SOLID	2
4	SHELL	3
5	FACE	4
6	WIRE	5
7	EDGE	6
8	VERTEX	7

- The argument of type 0 (*COMPOUND*) can include any number of shapes of an arbitrary type (0, 1... 7).
- The argument should not be self-interfered, i.e. all sub-shapes of the argument that have geometrical coincidence through any topological entities (vertices, edges, faces) must share these entities.
- There are no restrictions on the type of underlying geometry of the shapes. The faces or edges of arguments S_i can have underlying geometry of any type supported by Open CASCADE Technology modeling algorithms (in terms of *GeomAbs_CurveType* and *GeomAbs_SurfaceType*).
- The faces or edges of the arguments should have underlying geometry with continuity that is not less than C1.

4.2 Shapes

The information about Shapes is stored in structure *BOPDS_ShapeInfo*. The objects of type *BOPDS_ShapeInfo* are stored in the container of array type. The array allows getting the access to the information by an index (DS index). The structure *BOPDS_ShapeInfo* has the following contents:

Name	Contents
<i>myShape</i>	Shape itself
<i>myType</i>	Type of shape
<i>myBox</i>	3D bounding box of the shape
<i>mySubShapes</i>	List of DS indices of sub-shapes
<i>myReference</i>	Storage for some auxiliary information
<i>myFlag</i>	Storage for some auxiliary information

4.3 Interferences

The information about interferences is stored in the instances of classes that are inherited from class *BOPDS_Interf*.

Name	Contents
<i>BOPDS_Interf</i>	Root class for interference
<i>Index1</i>	DS index of the shape 1
<i>Index2</i>	DS index of the shape 2
<i>BOPDS_InterfVV</i>	Storage for Vertex/Vertex interference
<i>BOPDS_InterfVE</i>	Storage for Vertex/Edge interference
<i>myParam</i>	The value of parameter of the point of the vertex on the curve of the edge
<i>BOPDS_InterfVF</i>	Storage for Vertex/Face interference
<i>myU, myV</i>	The value of parameters of the point of the vertex on the surface of the face
<i>BOPDS_InterfEE</i>	Storage for Edge/Edge interference
<i>myCommonPart</i>	Common part (in terms of <i>IntTools_CommonPart</i>)
<i>BOPDS_InterfEF</i>	Storage for Edge/Face interference
<i>myCommonPart</i>	Common part (in terms of <i>IntTools_CommonPart</i>)
<i>BOPDS_InterfFF</i>	Storage for Face/Face interference
<i>myTolR3D, myTolR2D</i>	The value of tolerances of curves (points) reached in 3D and 2D
<i>myCurves</i>	Intersection Curves (in terms of <i>BOPDS_Curve</i>)
<i>myPoints</i>	Intersection Points (in terms of <i>BOPDS_Point</i>)
<i>BOPDS_InterfVZ</i>	Storage for Vertex/Solid interference
<i>BOPDS_InterfEZ</i>	Storage for Edge/Solid interference
<i>BOPDS_InterfFZ</i>	Storage for Face/Solid interference
<i>BOPDS_InterfZZ</i>	Storage for Solid/Solid interference

The Figure shows inheritance diagram for *BOPDS_Interf* classes.




Figure 21: BOPDS_Interf classes

4.4 Pave, PaveBlock and CommonBlock

The information about the pave is stored in objects of type *BOPDS_Pave*.

Name	Contents
<i>BOPDS_Pave</i>	
<i>myIndex</i>	DS index of the vertex
<i>myParam</i>	Value of the parameter of the 3D point of vertex on curve.

The information about pave blocks is stored in objects of type *BOPDS_PaveBlock*.

Name	Contents
<i>BOPDS_PaveBlock</i>	
<i>myEdge</i>	DS index of the edge produced from the pave block
<i>myOriginalEdge</i>	DS index of the source edge
<i>myPave1</i>	Pave 1 (in terms of <i>BOPDS_Pave</i>)
<i>myPave2</i>	Pave 2 (in terms of <i>BOPDS_Pave</i>)
<i>myExtPaves</i>	The list of paves (in terms of <i>BOPDS_Pave</i>) that is used to store paves lying inside the pave block during intersection process
<i>myCommonBlock</i>	The reference to common block (in terms of <i>BOPDS_CommonBlock</i>) if the pave block is a common block
<i>myShrunkData</i>	The shrunk range of the pave block

- To be bound to an edge (or intersection curve) the structures of type *BOPDS_PaveBlock* are stored in one container of list type (*BOPDS_ListOfPaveBlock*).
- In case of edge, all the lists of pave blocks above are stored in one container of array type. The array allows getting the access to the information by index of the list of pave blocks for the edge. This index (if exists) is stored in the field *myReference*.

The information about common block is stored in objects of type *BOPDS_CommonBlock*.

Name	Contents
<i>BOPDS_CommonBlock</i>	

Name	Contents
<i>myPaveBlocks</i>	The list of pave blocks that are common in terms of Common Blocks
<i>myFaces</i>	The list of DS indices of the faces, on which the pave blocks lie.

4.5 Points and Curves

The information about intersection point is stored in objects of type *BOPDS_Point*.

Name	Contents
<i>BOPDS_Point</i>	
<i>myPnt</i>	3D point
<i>myPnt2D1</i>	2D point on the face1
<i>myPnt2D2</i>	2D point on the face2

The information about intersection curve is stored in objects of type *BOPDS_Curve*.

Name	Contents
<i>BOPDS_Curve</i>	
<i>myCurve</i>	The intersection curve (in terms of <i>IntTools_Curve</i>)
<i>myPaveBlocks</i>	The list of pave blocks that belong to the curve
<i>myBox</i>	The bounding box of the curve (in terms of <i>Bnd_Box</i>)

4.6 FacelInfo

The information about *FacelInfo* is stored in a structure *BOPDS_FacelInfo*. The structure *BOPDS_FacelInfo* has the following contents.

Name	Contents
<i>BOPDS_FacelInfo</i>	
<i>myPaveBlocksIn</i>	Pave blocks that have state In for the face
<i>myVerticesIn</i>	Vertices that have state In for the face
<i>myPaveBlocksOn</i>	Pave blocks that have state On for the face
<i>myVerticesOn</i>	Vertices that have state On for the face
<i>myPaveBlocksSc</i>	Pave blocks built up from intersection curves for the face
<i>myVerticesSc</i>	Vertices built up from intersection points for the face +

The objects of type *BOPDS_FacelInfo* are stored in one container of array type. The array allows getting the access to the information by index. This index (if exists) is stored in the field *myReference*.

5 Root Classes

5.1 Class *BOPAlgo_Options*

The class *BOPAlgo_Options* provides the following options for the algorithms:

- Set the appropriate memory allocator;
- Check the presence of the Errors and Warnings;
- Turn on/off the parallel processing;
- Set the additional tolerance for the operation;
- Break the operations by user request;
- Usage of Oriented Bounding boxes in the operation.

5.2 Class *BOPAlgo_Algo*

The class *BOPAlgo_Algo* provides the base interface for all algorithms:

- Perform the operation;
- Check the input data;
- Check the result.

6 Intersection Part

Intersection Part (IP) is used to

- Initialize the Data Structure;
- Compute interferences between the arguments (or their sub-shapes);
- Compute same domain vertices, edges;
- Build split edges;
- Build section edges;
- Build p-curves;
- Store all obtained information in DS.

IP is implemented in the class *BOPAlgo_PaveFiller*.




Figure 22: Diagram for Class *BOPAlgo_PaveFiller*

The description provided in the next paragraphs is coherent with the implementation of the method *BOPAlgo_PaveFiller::Perform()*.

6.1 Initialization

The input data for the step is the Arguments. The description of initialization step is shown in the Table.

No	Contents	Implementation
1	Initialization the array of shapes (in terms of Shapes). Filling the array of shapes.	<i>BOPDS_DS::Init()</i>
2	Initialization the array pave blocks (in terms of Pave , PaveBlock , CommonBlock)	<i>BOPDS_DS::Init()</i>
3	Initialization of intersection Iterator. The intersection Iterator is the object that computes intersections between sub-shapes of the arguments in terms of bounding boxes. The intersection Iterator provides approximate number of the interferences for given type (in terms of Interferences)	<i>BOPDS_Iterator</i>
4	Initialization of intersection Context. The intersection Context is an object that contains geometrical and topological toolkit (classifiers, projectors, etc). The intersection Context is used to cache the tools to increase the algorithm performance.	<i>IntTools_Context</i>

6.2 Compute Vertex/Vertex Interferences

The input data for this step is the DS after the [Initialization](#). The description of this step is shown in the table :

No	Contents	Implementation
1	Initialize array of Vertex/Vertex interferences.	<i>BOPAlgo_PaveFiller::PerformVV()</i>
2	Access to the pairs of interfered shapes $(nVi, nVj)k, k=0, 1 \dots nk$, where nVi and nVj are DS indices of vertices Vi and Vj and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Compute the connexity chains of interfered vertices $nV1C, nV2C \dots nVnC)k, C=0, 1 \dots nCs$, where nCs is the number of the connexity chains	<i>BOPAlgo_Tools::MakeBlocksCnx()</i>
4	Build new vertices from the chains $VNc. C=0, 1 \dots nCs$.	<i>BOPAlgo_PaveFiller::PerformVV()</i>
5	Append new vertices in DS.	<i>BOPDS_DS::Append()</i>
6	Append same domain vertices in DS.	<i>BOPDS_DS::AddShapeSD()</i>
7	Append Vertex/Vertex interferences in DS.	<i>BOPDS_DS::AddInterf()</i>

- The pairs of interfered vertices are: $(nV11, nV12), (nV11, nV13), (nV12, nV13), (nV13, nV15), (nV13, nV14), (nV14, nV15), (nV21, nV22), (nV21, nV23), (nV22, nV23)$;
- These pairs produce two chains: $(nV11, nV12, nV13, nV14, nV15)$ and $(nV21, nV22, nV23)$;
- Each chain is used to create a new vertex, $VN1$ and $VN2$, correspondingly.

The example of connexity chains of interfered vertices is given in the image:




Figure 23: Connexity chains of interfered vertices

6.3 Compute Vertex/Edge Interferences

The input data for this step is the DS after computing Vertex/Vertex interferences.

No	Contents	Implementation
1	Initialize array of Vertex/Edge interferences	<i>BOPAlgo_PaveFiller::PerformVE()</i>
2	Access to the pairs of interfered shapes $(nVi, nEj)k k=0, 1 \dots nk$, where nVi is DS index of vertex Vi , nEj is DS index of edge Ej and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Compute paves. See Vertex/Edge Interference	<i>BOPInt_Context::ComputeVE()</i>

No	Contents	Implementation
4	Initialize pave blocks for the edges E_j involved in the interference	<i>BOPDS_DS::ChangePaveBlocks()</i>
5	Append the paves into the pave blocks in terms of Pave , Pave↔Block and CommonBlock	<i>BOPDS_PaveBlock::AppendExtPave()</i>
6	Append Vertex/Edge interferences in DS	<i>BOPDS_DS::AddInterf()</i>

6.4 Update Pave Blocks

The input data for this step is the DS after computing Vertex/Edge Interferences.

No	Contents	Implementation
1	Each pave block PB containing internal paves is split by internal paves into new pave blocks $PBN1, PBN2 \dots PBNn$. PB is replaced by new pave blocks $PBN1, PBN2 \dots PBNn$ in the DS.	<i>BOPDS_DS::UpdatePaveBlocks()</i>

6.5 Compute Edge/Edge Interferences

The input data for this step is the DS after updating Pave Blocks.

No	Contents	Implementation
1	Initialize array of Edge/Edge interferences	<i>BOPAlgo_PaveFiller::PerformEE()</i>
2	Access to the pairs of interfered shapes $(nEi, nEj)k, k=0, 1 \dots nk$, where nEi is DS index of the edge Ei , nEj is DS index of the edge Ej and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Initialize pave blocks for the edges involved in the interference, if it is necessary.	<i>BOPDS_DS::ChangePaveBlocks()</i>
4	Access to the pave blocks of interfered shapes: $(PBi1, P↔Bi2 \dots PBiNi)$ for edge Ei and $(PBj1, PBj2 \dots PBjNj)$ for edge Ej	<i>BOPAlgo_PaveFiller::PerformEE()</i>
5	Compute shrunk data for pave blocks in terms of Pave , PaveBlock and CommonBlock , if it is necessary.	<i>BOPAlgo_PaveFiller::FillShrunkData()</i>
6	Compute Edge/Edge interference for pave blocks $PBix$ and $PBiy$. The result of the computation is a set of objects of type <i>IntTools_CommonPart</i>	<i>IntTools_EdgeEdge</i>
7.↔ 1	For each <i>CommonPart</i> of type VERTEX: Create new vertices VNi ($i=1, 2 \dots NbVN$), where $NbVN$ is the number of new vertices. Intersect the vertices VNi using the steps Initialization and compute Vertex/Vertex interferences as follows: a) create a new object PFn of type <i>BOPAlgo_↔PaveFiller</i> with its own DS; b) use new vertices VNi ($i=1, 2 \dots NbVN$), $NbVN$ as arguments (in terms of <i>TopoDs_↔Shape</i>) of PFn ; c) invoke method <i>Perform()</i> for PFn . The resulting vertices $VNXi$ ($i=1, 2 \dots NbVNX$), where $NbVNX$ is the number of vertices, are obtained via mapping between VNi and the results of PVn .	<i>BOPTools_Tools::MakeNewVertex()</i>
7.↔ 2	For each <i>CommonPart</i> of type EDGE: Compute the coinciding connexity chains of pave blocks $(PB1C, PB2C \dots P↔NnC)k, C=0, 1 \dots nCs$, where nCs is the number of the connexity chains. Create common blocks $(CBc, C=0, 1 \dots nCs)$ from the chains. Attach the common blocks to the pave blocks.	<i>BOPAlgo_Tools::PerformCommonBlocks()</i>

No	Contents	Implementation
8	Post-processing. Append the paves of VNX_i into the corresponding pave blocks in terms of Pave , PaveBlock and CommonBlock	<i>BOPDS_PaveBlock::AppendExtPave()</i>
9	Split common blocks CBc by the paves.	<i>BOPDS_DS::UpdateCommonBlock()</i>
10	Append Edge/Edge interferences in the DS.	<i>BOPDS_DS::AddInterf()</i>

The example of coinciding chains of pave blocks is given in the image:




Figure 24: Coinciding chains of pave blocks

- The pairs of coincided pave blocks are: (PB_{11}, PB_{12}) , (PB_{11}, PB_{13}) , (PB_{12}, PB_{13}) , (PB_{21}, PB_{22}) , (PB_{21}, PB_{23}) , (PB_{22}, PB_{23}) .
- The pairs produce two chains: $(PB_{11}, PB_{12}, PB_{13})$ and $(PB_{21}, PB_{22}, PB_{23})$.

6.6 Compute Vertex/Face Interferences

The input data for this step is the DS after computing Edge/Edge interferences.

No	Contents	Implementation
1	Initialize array of Vertex/Face interferences	<i>BOPAlgo_PaveFiller::PerformVF()</i>
2	Access to the pairs of interfered shapes $(nVi, nFj)_k$, $k=0, 1 \dots nk$, where nVi is DS index of the vertex Vi , nFj is DS index of the edge Fj and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Compute interference See Vertex/Face Interference	<i>BOPInt_Context::ComputeVF()</i>
4	Append Vertex/Face interferences in the DS	<i>BOPDS_DS::AddInterf()</i>
5	Repeat steps 2-4 for each new vertex VNX_i ($i=1, 2 \dots NbVNX$), where $NbVNX$ is the number of vertices.	<i>BOPAlgo_PaveFiller::TreatVerticesEE()</i>

6.7 Compute Edge/Face Interferences

The input data for this step is the DS after computing Vertex/Face Interferences.

No	Contents	Implementation
1	Initialize array of Edge/Face interferences	<i>BOPAlgo_PaveFiller::PerformEF()</i>
2	Access to the pairs of interfered shapes (nE_i, nF_j), $k=0, 1 \dots nk$, where nE_i is DS index of edge E_i , nF_j is DS index of face F_j and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Initialize pave blocks for the edges involved in the interference, if it is necessary.	<i>BOPDS_DS::ChangePaveBlocks()</i>
4	Access to the pave blocks of interfered edge ($PB_{i1}, PB_{i2} \dots PB_{iN_i}$) for edge E_i	<i>BOPAlgo_PaveFiller::PerformEF()</i>
5	Compute shrunk data for pave blocks (in terms of Pave , PaveBlock and CommonBlock) if it is necessary.	<i>BOPAlgo_PaveFiller::FillShrunkData()</i>
6	Compute Edge/Face interference for pave block PB_{ix} , and face nF_j . The result of the computation is a set of objects of type <i>IntTools_CommonPart</i>	<i>IntTools_EdgeFace</i>
7.↔ 1	For each <i>CommonPart</i> of type VERTEX: Create new vertices VN_i ($i=1, 2 \dots NbVN$), where $NbVN$ is the number of new vertices. Merge vertices VN_i as follows: a) create new object PF_n of type <i>BOP↔Algo_PaveFiller</i> with its own DS; b) use new vertices VN_i ($i=1, 2 \dots NbVN$), $NbVN$ as arguments (in terms of <i>TopoDs_Shape</i>) of PF_n ; c) invoke method <i>Perform()</i> for PF_n . The resulting vertices VNX_i ($i=1, 2 \dots NbVNX$), where $NbVNX$ is the number of vertices, are obtained via mapping between VN_i and the results of PV_n .	<i>BOPTools_Tools::MakeNewVertex()</i> and <i>BOP↔Algo_PaveFiller::PerformVertices1()</i>
7.↔ 2	For each <i>CommonPart</i> of type EDGE: Create common blocks (CB_c , $C=0, 1 \dots nCs$) from pave blocks that lie on the faces. Attach the common blocks to the pave blocks.	<i>BOPAlgo_Tools::PerformCommonBlocks()</i>
8	Post-processing. Append the paves of VNX_i into the corresponding pave blocks in terms of Pave , PaveBlock and CommonBlock .	<i>BOPDS_PaveBlock::AppendExtPave()</i>
9	Split pave blocks and common blocks CB_c by the paves.	<i>BOPAlgo_PaveFiller::PerformVertices1()</i> , <i>BOPD↔S_DS::UpdatePaveBlock()</i> and <i>BOPDS_DS↔:UpdateCommonBlock()</i>
10	Append Edge/Face interferences in the DS	<i>BOPDS_DS::AddInterf()</i>
11	Update <i>FaceInfo</i> for all faces having EF common parts.	<i>BOPDS_DS::UpdateFaceInfoIn()</i>

6.8 Build Split Edges

The input data for this step is the DS after computing Edge/Face Interferences.

For each pave block PB take the following steps:

No	Contents	Implementation
1	Get the real pave block PBR , which is equal to PB if PB is not a common block and to PB_1 if PB is a common block. PB_1 is the first pave block in the pave blocks list of the common block. See Pave , PaveBlock and CommonBlock .	<i>BOPAlgo_PaveFiller::MakeSplitEdges()</i>
2	Build the split edge Esp using the information from DS and PBR .	<i>BOPTools_Tools::MakeSplitEdge()</i>
3	Compute <i>BOPDS_ShapeInfo</i> contents for Esp	<i>BOPAlgo_PaveFiller::MakeSplitEdges()</i>
4	Append <i>BOPDS_ShapeInfo</i> contents to the DS	<i>BOPDS_DS::Append()</i>

6.9 Compute Face/Face Interferences

The input data for this step is DS after building Split Edges.

No	Contents	Implementation
1	Initialize array of Face/Face interferences	<i>BOPAlgo_PaveFiller::PerformFF()</i>
2	Access to the pairs of interfered shapes $(nFi, nFj)k, k=0, 1 \dots nk$, where nFi is DS index of edge Fi , nFj is DS index of face Fj and nk is the number of pairs.	<i>BOPDS_Iterator</i>
3	Compute Face/Face interference	<i>IntTools_FaceFace</i>
4	Append Face/Face interferences in the DS.	<i>BOPDS_DS::AddInterf()</i>

6.10 Build Section Edges

The input data for this step is the DS after computing Face/Face interferences.

No	Contents	Implementation
1	For each Face/Face interference nFi, nFj , retrieve FaceInfo . Create draft vertices from intersection points $VPk (k=1, 2 \dots, NbVP)$, where $NbVP$ is the number of new vertices, and the draft vertex VPk is created from an intersection point if $VPk Vm (m = 0, 1, 2 \dots NbVm)$, where Vm is an existing vertex for the faces nFi and nFj (<i>On</i> or <i>In</i> in terms of <i>TopoDs_Shape</i>), $NbVm$ is the number of vertices existing on faces nFi and nFj and – means non-coincidence in terms of Vertex/Vertex interference .	<i>BOPAlgo_PaveFiller::MakeBlocks()</i>
2.↔ 1	For each intersection curve $Cijk$ Create paves PVc for the curve using existing vertices, i.e. vertices <i>On</i> or <i>In</i> (in terms of <i>FaceInfo</i>) for faces nFi and nFj . Append the paves PVc	<i>BOPAlgo_PaveFiller::PutPaveOnCurve()</i> and <i>BO↔PDS_PaveBlock::AppendExtPave()</i>
2.↔ 2	Create technological vertices Vt , which are the bounding points of an intersection curve (with the value of tolerance $Tol(Cijk)$). Each vertex Vt with parameter Tt on curve $Cijk$ forms pave PVt on curve $Cijk$. Append technological paves.	<i>BOPAlgo_PaveFiller::PutBoundPaveOnCurve()</i>
2.↔ 3	Create pave blocks PBk for the curve using paves $(k=1, 2 \dots, NbPB)$, where $NbPB$ is the number of pave blocks	<i>BOPAlgo_PaveFiller::MakeBlocks()</i>
2.↔ 4	Build draft section edges ESk using the pave blocks $(k=1, 2 \dots, NbES)$, where $NbES$ is the number of draft section edges The draft section edge is created from a pave block PBk if PBk has state <i>In</i> or <i>On</i> for both faces nFi and nFj and $PBk PBm (m=0, 1, 2 \dots NbPBm)$, where PBm is an existing pave block for faces nFi and nFj (<i>On</i> or <i>In</i> in terms of <i>FaceInfo</i>), $NbVm$ is the number of existing pave blocks for faces nFi and nFj and – means non-coincidence (in terms of Vertex/Face interference).	<i>BOPTools_Tools::MakeEdge()</i>

No	Contents	Implementation
3	Intersect the draft vertices VP_k ($k=1, 2, \dots, NbVP$) and the draft section edges ES_k ($k=1, 2, \dots, NbES$). For this: a) create new object PF_n of type $BO \leftrightarrow PAlgo_PaveFiller$ with its own DS; b) use vertices VP_k and edges ES_k as arguments (in terms of Arguments) of PF_n ; c) invoke method $Perform()$ for PF_n . Resulting vertices VPX_k ($k=1, 2, \dots, NbVPX$) and edges ESX_k ($k=1, 2, \dots, NbESX$) are obtained via mapping between VP_k , ES_k and the results of PV_n .	$BOPAlgo_PaveFiller::PostTreatFF()$
4	Update face info (sections about pave blocks and vertices)	$BOPAlgo_PaveFiller::PerformFF()$

6.11 Build P-Curves

The input data for this step is the DS after building section edges.

No	Contents	Implementation
1	For each Face/Face interference nFi and nFj build p-Curves on nFi and nFj for each section edge ESX_k .	$BOPAlgo_PaveFiller::MakePCurves()$
2	For each pave block that is common for faces nFi and nFj build p-Curves on nFi and nFj .	$BOPAlgo_PaveFiller::MakePCurves()$

6.12 Process Degenerated Edges

The input data for this step is the DS after building P-curves.

No	Contents	Implementation
	For each degenerated edge ED having vertex VD	$BOPAlgo_PaveFiller::ProcessDE()$
1	Find pave blocks PBi ($i=1, 2, \dots, NbPB$), where $NbPB$ is the number of pave blocks, that go through vertex VD .	$BOPAlgo_PaveFiller::FindPaveBlocks()$
2	Compute paves for the degenerated edge ED using a 2D curve of ED and a 2D curve of PBi . Form pave blocks $PBDi$ ($i=1, 2, \dots, NbPBD$), where $NbPBD$ is the number of the pave blocks for the degenerated edge ED	$BOPAlgo_PaveFiller::FillPaves()$
3	Build split edges $ESDi$ ($i=1, 2, \dots, NbESD$), where ESD is the number of split edges, using the pave blocks $PBDi$	$BOPAlgo_PaveFiller::MakeSplitEdge()$

7 General description of the Building Part

Building Part (BP) is used to

- Build the result of the operation
- Provide history information (in terms of *::Generated()*, *::Modified()* and *::IsDeleted()*) BP uses the DS prepared by *BOPAlgo_PaveFiller* described at chapter 5 as input data. BP is implemented in the following classes:
- *BOPAlgo_Builder* – for the General Fuse operator (GFA).
- *BOPAlgo_BOP* – for the Boolean Operation operator (BOA).
- *BOPAlgo_Section* – for the Section operator (SA).
- *BOPAlgo_MakerVolume* – for the Volume Maker operator.
- *BOPAlgo_Splitter* – for the Splitter operator.
- *BOPAlgo_CellsBuilder* – for the Cells Builder operator.




Figure 25: Diagram for BP classes

The class *BOPAlgo_BuilderShape* provides the interface for algorithms that have:

- A Shape as the result;
- History information (in terms of *::Generated()*, *::Modified()* and *::IsDeleted()*).

8 General Fuse Algorithm

8.1 Arguments

The arguments of the algorithm are shapes (in terms of *TopoDS_Shape*). The main requirements for the arguments are described in [Data Structure](#) chapter.

8.2 Results

During the operation argument S_i can be split into several parts $S_{i1}, S_{i2} \dots S_{i1NbSp}$, where $NbSp$ is the number of parts. The set $(S_{i1}, S_{i2} \dots S_{i1NbSp})$ is an image of argument S_i .

- The result of the General Fuse operation is a compound. Each sub-shape of the compound corresponds to the certain argument shape $S_1, S_2 \dots S_n$ and has shared sub-shapes in accordance with interferences between the arguments.
- For the arguments of the type EDGE, FACE, SOLID the result contains split parts of the argument.
- For the arguments of the type WIRE, SHELL, COMPSOLID, COMPOUND the result contains the image of the shape of the corresponding type (i.e. WIRE, SHELL, COMPSOLID or COMPOUND). The types of resulting shapes depend on the type of the corresponding argument participating in the operation. See the table below:

No	Type of argument	Type of resulting shape	Comments
1	COMPOUND	COMPOUND	The resulting COMPOUND is built from images of sub-shapes of type COMPOUND COMPSOLID, SHELL, WIRE and VERTEX. Sets of split sub-shapes of type SOLID, FACE, EDGE.
2	COMPSOLID	COMPSOLID	The resulting COMPSOLID is built from split SOLIDs.
3	SOLID	Set of split SOLIDs	
4	SHELL	SHELL	The resulting SHELL is built from split FACEs
5	FACE	Set of split FACEs	
6	WIRE	WIRE	The resulting WIRE is built from split EDGEs
7	EDGE	Set of split EDGEs	
8	VERTEX	VERTEX	

8.3 Options

The General Fuse algorithm has a set of options, which allow speeding-up the operation and improving the quality of the result:

- Parallel processing option allows running the algorithm in parallel mode;
- Fuzzy option allows setting the additional tolerance for the operation;
- Safe input shapes option allows preventing modification of the input shapes;
- Gluing option allows speeding-up the intersection of the arguments;
- Possibility to disable the check for the inverted solids among input shapes;
- Usage of Oriented Bounding Boxes in the operation;
- History support.

For more detailed information on these options please see the [Advanced options](#) section.

8.4 Usage

The following example illustrates how to use the GF algorithm:

Usage of the GF algorithm on C++ level

```

BOPAlgo_Builder aBuilder;
// Setting arguments
TopTools_ListOfShape aLSObjects = ...; // Objects
aBuilder.SetArguments(aLSObjects);

// Setting options for GF

// Set parallel processing mode (default is false)
Standard_Boolean bRunParallel = Standard_True;
aBuilder.SetRunParallel(bRunParallel);

// Set Fuzzy value (default is Precision::Confusion())
Standard_Real aFuzzyValue = 1.e-5;
aBuilder.SetFuzzyValue(aFuzzyValue);

// Set safe processing mode (default is false)
Standard_Boolean bSafeMode = Standard_True;
aBuilder.SetNonDestructive(bSafeMode);

// Set Gluing mode for coinciding arguments (default is off)
BOPAlgo_GlueEnum aGlue = BOPAlgo_GlueShift;
aBuilder.SetGlue(aGlue);

// Disabling/Enabling the check for inverted solids (default is true)
Standard_Boolean bCheckInverted = Standard_False;
aBuilder.SetCheckInverted(bCheckInverted);

// Set OBB usage (default is false)
Standard_Boolean bUseOBB = Standard_True;
aBuilder.SetUseOBB(buseobb);

// Perform the operation
aBuilder.Perform();

// Check for the errors
if (aBuilder.HasErrors())
{
    return;
}

// Check for the warnings
if (aBuilder.HasWarnings())
{
    // treatment of the warnings
    ...
}

// result of the operation
const TopoDS_Shape& aResult = aBuilder.Shape();

```

Usage of the GF algorithm on Tcl level

```

# prepare the arguments
box b1 10 10 10
box b2 3 4 5 10 10 10
box b3 5 6 7 10 10 10

# clear inner contents
bclearobjects; bcleartools;

# set the arguments
baddobjects b1 b2 b3

# setting options for GF

# set parallel processing mode (default is 0)
brunparallel 1

# set Fuzzy value
bfuzzyvalue 1.e-5

# set safe processing mode (default is 0)
bnondestructive 1

# set gluing mode (default is 0)
bglue 1

# set check for inverted (default is 1)

```

```

bcheckinverted 0

# set obb usage (default is 0)
buseobb 1

# perform intersection
bfillds

# perform GF operaton
bbuild result

```

8.5 Examples

Please, have a look at the examples, which can help to better understand the definitions.

8.5.1 Case 1: Three edges intersecting at a point

Let us consider three edges: E_1 , E_2 and E_3 that intersect in one 3D point.




Figure 26: Three Intersecting Edges

The result of the GFA operation is a compound containing 6 new edges: E_{11} , E_{12} , E_{21} , E_{22} , E_{31} , and E_{32} . These edges have one shared vertex Vn_1 .

In this case:

- The argument edge E_1 has resulting split edges E_{11} and E_{12} (image of E_1).
- The argument edge E_2 has resulting split edges E_{21} and E_{22} (image of E_2).
- The argument edge E_3 has resulting split edges E_{31} and E_{32} (image of E_3).

8.5.2 Case 2: Two wires and an edge

Let us consider two wires W_1 (E_{w11} , E_{w12} , E_{w13}) and W_2 (E_{w21} , E_{w22} , E_{w23}) and edge E_1 .




Figure 27: Two wires and an edge

The result of the GF operation is a compound consisting of 2 wires: W_{n1} ($E_{w11}, E_{n1}, E_{n2}, E_{n3}, E_{w13}$) and W_{n2} ($E_{w21}, E_{n2}, E_{n3}, E_{n4}, E_{w23}$) and two edges: E_{11} and E_{12} .

In this case :

- The argument W_1 has image W_{n1} .
- The argument W_2 has image W_{n2} .
- The argument edge E_1 has split edges E_{11} and E_{12} . (image of E_1). The edges $E_{n1}, E_{n2}, E_{n3}, E_{n4}$ and vertex V_{n1} are new shapes created during the operation. Edge E_{w12} has split edges E_{n1}, E_{n2} and E_{n3} and edge E_{w22} has split edges E_{n2}, E_{n3} and E_{n4} .

8.5.3 Case 3: An edge intersecting with a face

Let us consider edge E_1 and face F_2 :




Figure 28: An edge intersecting with a face

The result of the GF operation is a compound consisting of 3 shapes:

- Split edge parts E_{11} and E_{12} (image of E_1).
- New face F_{21} with internal edge E_{12} (image of F_2).

8.5.4 Case 4: An edge lying on a face

Let us consider edge E_1 and face F_2 :




Figure 29: An edge lying on a face

The result of the GF operation is a compound consisting of 5 shapes:

- Split edge parts E_{11} , E_{12} and E_{13} (image of E_1).
- Split face parts F_{21} and F_{22} (image of F_2).

8.5.5 Case 5: An edge and a shell

Let us consider edge E_1 and shell Sh_2 that consists of 2 faces: F_{21} and F_{22}




Figure 30: An edge and a shell

The result of the GF operation is a compound consisting of 5 shapes:

- Split edge parts E_{11} , E_{12} , E_{13} and E_{14} (image of E_1).
- Image shell Sh_{21} (that contains split face parts F_{211} , F_{212} , F_{221} and F_{222}).

8.5.6 Case 6: A wire and a shell

Let us consider wire W_1 (E_1 , E_2 , E_3 , E_4) and shell Sh_2 (F_{21} , F_{22}).




Figure 31: A wire and a shell

The result of the GF operation is a compound consisting of 2 shapes:

- Image wire W_{11} that consists of split edge parts from wire W_1 : E_{11} , E_{12} , E_{13} and E_{14} .
- Image shell Sh_{21} that contains split face parts: F_{211} , F_{212} , F_{213} , F_{221} , F_{222} and F_{223} .

8.5.7 Case 7: Three faces

Let us consider 3 faces: F_1 , F_2 and F_3 .




Figure 32: Three faces

The result of the GF operation is a compound consisting of 7 shapes:

- Split face parts: $Fn1$, $Fn2$, $Fn3$, $Fn4$, $Fn5$, $Fn6$ and $Fn7$.

8.5.8 Case 8: A face and a shell

Let us consider shell $Sh1$ ($F11$, $F12$, $F13$) and face $F2$.




Figure 33: A face and a shell

The result of the GF operation is a compound consisting of 4 shapes:

- Image shell $Sh11$ that consists of split face parts from shell $Sh1$: $Fn1$, $Fn2$, $Fn3$, $Fn4$, $Fn5$ and $Fn6$.
- Split parts of face $F2$: $Fn3$, $Fn6$ and $Fn7$.

8.5.9 Case 9: A shell and a solid

Let us consider shell $Sh1$ ($F11$, $F12$... $F16$) and solid $So2$.




Figure 34: A shell and a solid: arguments

The result of the GF operation is a compound consisting of 2 shapes:

- Image shell $Sh11$ consisting of split face parts of $Sh1$: $Fn1, Fn2 \dots Fn8$.
- Solid $So21$ with internal shell. (image of $So2$).




Figure 35: A shell and a solid: results

8.5.10 Case 10: A compound and a solid

Let us consider compound $Cm1$ consisting of 2 solids $So11$ and $So12$ and solid $So2$.



Figure 36: A compound and a solid: arguments

The result of the GF operation is a compound consisting of 4 shapes:

- Image compound *Cm11* consisting of split solid parts from *So11* and *So12* (*Sn1*, *Sn2*, *Sn3*, *Sn4*).
- Split parts of solid *So2* (*Sn2*, *Sn3*, *Sn5*).




Figure 37: A compound and a solid: results

8.6 Class BOPAlgo_Builder

GFA is implemented in the class *BOPAlgo_Builder*.

8.6.1 Fields

The main fields of the class are described in the Table:

Name	Contents
<i>myPaveFiller</i>	Pointer to the <i>BOPAlgo_PaveFiller</i> object
<i>myDS</i>	Pointer to the <i>BOPDS_DS</i> object

Name	Contents
<i>myContext</i>	Pointer to the intersection Context
<i>myImages</i>	The Map between the source shape and its images
<i>myShapesSD</i>	The Map between the source shape (or split part of source shape) and the shape (or part of shape) that will be used in result due to same domain property.

8.6.2 Initialization

The input data for this step is a *BOPAlgo_PaveFiller* object (in terms of [Intersection](#)) at the state after [Processing of degenerated edges](#) with the corresponding DS.

No	Contents	Implementation
1	Check the readiness of the DS and <i>BOPAlgo_PaveFiller</i> .	<i>BOPAlgo_Builder::CheckData()</i>
2	Build an empty result of type Compound.	<i>BOPAlgo_Builder::Prepare()</i>

8.6.3 Build Images for Vertices

The input data for this step is *BOPAlgo_Builder* object after Initialization.

No	Contents	Implementation
1	Fill <i>myShapesSD</i> by SD vertices using the information from the DS.	<i>BOPAlgo_Builder::FillImagesVertices()</i>

8.6.4 Build Result of Type Vertex

The input data for this step is *BOPAlgo_Builder* object after building images for vertices and *Type*, which is the shape type (*TopAbs_VERTEX*).

No	Contents	Implementation
1	For the arguments of type <i>Type</i> . If there is an image for the argument: add the image to the result. If there is no image for the argument: add the argument to the result.	<i>BOPAlgo_Builder::BuildResult()</i>

8.6.5 Build Images for Edges

The input data for this step is *BOPAlgo_Builder* object after building result of type vertex.

No	Contents	Implementation
1	For all pave blocks in the DS. Fill <i>myImages</i> for the original edge <i>E</i> by split edges <i>ESPi</i> from pave blocks. In case of common blocks on edges, use edge <i>ESPSDj</i> that corresponds to the leading pave block and fill <i>myShapesSD</i> by the pairs <i>ESPi/ESPSDj</i> .	<i>BOPAlgo_Builder::FillImagesEdges()</i>

8.6.6 Build Result of Type Edge

This step is the same as [Building Result of Type Vertex](#), but for the type *Edge*.

8.6.7 Build Images for Wires

The input data for this step is:

- *BOPAlgo_Builder* object after building result of type *Edge*;
- Original Shape – Wire
- *Type* – the shape type (*TopAbs_WIRE*).

No	Contents	Implementation
1	For all arguments of the type <i>Type</i> . Create a container C of the type <i>Type</i> .	<i>BOPAlgo_Builder::FillImagesContainers()</i>
2	Add to C the images or non-split parts of the <i>Original Shape</i> , taking into account its orientation.	<i>BOPAlgo_Builder::FillImagesContainers()</i> <i>BOPToolsTools::IsSplitToReverse()</i>
3	Fill <i>myImages</i> for the <i>Original Shape</i> by the information above.	<i>BOPAlgo_Builder::FillImagesContainers()</i>

8.6.8 Build Result of Type Wire

This step is the same as [Building Result of Type Vertex](#) but for the type *Wire*.

8.6.9 Build Images for Faces

The input data for this step is *BOPAlgo_Builder* object after building result of type *Wire*.

No	Contents	Implementation
1	Build Split Faces for all interfered DS shapes <i>Fi</i> of type <i>FACE</i> .	
1.↔ 1	Collect all edges or their images of <i>Fi(ESPIj)</i> .	<i>BOPAlgo_Builder::BuildSplitFaces()</i>
1.↔ 2	Impart to <i>ESPIj</i> the orientation to be coherent with the original one.	<i>BOPAlgo_Builder::BuildSplitFaces()</i>
1.↔ 3	Collect all section edges <i>SEk</i> for <i>Fi</i> .	<i>BOPAlgo_Builder::BuildSplitFaces()</i>
1.↔ 4	Build split faces for <i>Fi (Fi1, Fi2... FiNbSp)</i> , where <i>NbSp</i> is the number of split parts (see Building faces from a set of edges for more details).	<i>BOPAlgo_BuilderFace</i>
1.↔ 5	Impart to (<i>Fi1, Fi2... FiNbSp</i>) the orientation coherent with the original face <i>Fi</i> .	<i>BOPAlgo_Builder::BuildSplitFaces()</i>
1.↔ 6	Fill the map <i>mySplits</i> with <i>Fi/(Fi1, Fi2... FiNbSp)</i>	<i>BOPAlgo_Builder::BuildSplitFaces()</i>
2	Fill Same Domain faces	<i>BOPAlgo_Builder::FillSameDomainFaces</i>
2.↔ 1	Find and collect in the contents of <i>mySplits</i> the pairs of same domain split faces (<i>Fij, Fkl</i>) <i>m</i> , where <i>m</i> is the number of pairs.	<i>BOPAlgo_Builder::FillSameDomainFaces</i> <i>BOPToolsTools::AreFacesSameDomain()</i>
2.↔ 2	Compute the connexity chains 1) of same domain faces (<i>F1C, F2C... FnC</i>) <i>k</i> , <i>C=0, 1... nCs</i> , where <i>nCs</i> is the number of connexity chains.	<i>BOPAlgo_Builder::FillSameDomainFaces()</i>
2.↔ 3	Fill <i>myShapesSD</i> using the chains (<i>F1C, F2C... FnC</i>) <i>k</i>	<i>BOPAlgo_Builder::FillSameDomainFaces()</i>
2.↔ 4	Add internal vertices to split faces.	<i>BOPAlgo_Builder::FillSameDomainFaces()</i>
2.↔ 5	Fill <i>myImages</i> using <i>myShapesSD</i> and <i>mySplits</i> .	<i>BOPAlgo_Builder::FillSameDomainFaces()</i>

The example of chains of same domain faces is given in the image:




Figure 38: Chains of same domain faces

- The pairs of same domain faces are: (F_{11}, F_{21}) , (F_{22}, F_{31}) , (F_{41}, F_{51}) , (F_{41}, F_6) and (F_{51}, F_6) .
- The pairs produce the three chains: (F_{11}, F_{21}) , (F_{22}, F_{31}) and (F_{41}, F_{51}, F_6) .

8.6.10 Build Result of Type Face

This step is the same as [Building Result of Type Vertex](#) but for the type *Face*.

8.6.11 Build Images for Shells

The input data for this step is:

- *BOPAlgo_Builder* object after building result of type face;
- *Original Shape* – a Shell;
- *Type* – the type of the shape (*TopAbs_SHELL*).

The procedure is the same as for building images for wires.

8.6.12 Build Result of Type Shell

This step is the same as [Building Result of Type Vertex](#) but for the type *Shell*.

8.6.13 Build Images for Solids

The input data for this step is *BOPAlgo_Builder* object after building result of type *Shell*.

The following procedure is executed for all interfered DS shapes *Si* of type *SOLID*.

No	Contents	Implementation
1	Collect all images or non-split parts for all faces (FSP_{ij}) that have 3D state <i>In Si</i> .	<i>BOPAlgo_Builder::FillIn3DParts ()</i>
2	Collect all images or non-split parts for all faces of <i>Si</i>	<i>BOPAlgo_Builder::BuildSplitSolids()</i>
3	Build split solids for <i>Si</i> -> ($Si_1, Si_2 \dots Si_{NbSp}$), where <i>NbSp</i> is the number of split parts (see Building faces from a set of edges for more details)	<i>BOPAlgo_BuilderSolid</i>
4	Fill the map Same Domain solids <i>myShapesSD</i>	<i>BOPAlgo_Builder::BuildSplitSolids()</i>

No	Contents	Implementation
5	Fill the map <i>myImages</i>	<i>BOPAlgo_Builder::BuildSplitSolids()</i>
6	Add internal vertices to split solids	<i>BOPAlgo_Builder::FillInternalShapes()</i>

8.6.14 Build Result of Type Solid

This step is the same as [Building Result of Type Vertex](#), but for the type Solid.

8.6.15 Build Images for Type CompSolid

The input data for this step is:

- *BOPAlgo_Builder* object after building result of type solid;
- *Original Shape* – a Compsolid;
- *Type* – the type of the shape (*TopAbs_COMPSOLID*).

The procedure is the same as for building images for wires.

8.6.16 Build Result of Type Compsolid

This step is the same as [Building Result of Type Vertex](#), but for the type Compsolid.

8.6.17 Build Images for Compounds

The input data for this step is as follows:

- *BOPAlgo_Builder* object after building results of type *compsolid*;
- *Original Shape* – a Compound;
- *Type* – the type of the shape (*TopAbs_COMPOUND*).

The procedure is the same as for building images for wires.

8.6.18 Build Result of Type Compound

This step is the same as [Building Result of Type Vertex](#), but for the type Compound.

8.6.19 Post-Processing

The purpose of the step is to correct tolerances of the result to provide its validity in terms of *BRepCheck_Analyzer*.

The input data for this step is a *BOPAlgo_Builder* object after building result of type compound.

No	Contents	Implementation
1	Correct tolerances of vertices on curves	<i>BOPTools_Tools::CorrectPointOnCurve()</i>
2	Correct tolerances of edges on faces	<i>BOPTools_Tools::CorrectCurveOnSurface()</i>

9 Splitter Algorithm

The Splitter algorithm allows splitting a group of arbitrary shapes by another group of arbitrary shapes. It is based on the General Fuse algorithm, thus all options of the General Fuse (see [GF Options](#)) are also available in this algorithm.

9.1 Arguments

- The arguments of the Splitter algorithm are divided into two groups - *Objects* (shapes that will be split) and *Tools* (shapes, by which the *Objects* will be split);
- The requirements for the arguments (both for *Objects* and *Tools*) are the same as for the General Fuse algorithm - there can be any number of arguments of any type in each group, but each argument should be valid and not self-interfered.

9.2 Results

- The result of Splitter algorithm contains only the split parts of the shapes included into the group of *Objects*;
- The split parts of the shapes included only into the group of *Tools* are excluded from the result;
- If there are no shapes in the group of *Tools* the result of the operation will be equivalent to the result of General Fuse operation;
- The shapes can be split by other shapes from the same group (if these shapes are interfering).

9.3 Usage

9.3.1 API

On the low level the Splitter algorithm is implemented in class *BOPAlgo_Splitter*. The usage of this algorithm looks as follows:

```
BOPAlgo_Splitter aSplitter;
// Setting arguments and tools
TopTools_ListOfShape aLSObjects = ...; // Objects
TopTools_ListOfShape aLSTools = ...; // Tools
aSplitter.SetArguments(aLSObjects);
aSplitter.SetTools(aLSTools);

// Set options for the algorithm
// setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
// chapter)
...

// Perform the operation
aSplitter.Perform();
if (aSplitter.HasErrors()) { //check error status
    return;
}
//
const TopoDS_Shape& aResult = aSplitter.Shape(); // result of the operation
```

9.3.2 DRAW

The command *bsplit* implements the Splitter algorithm in DRAW. Similarly to the *bbuild* command for the General Fuse algorithm, the *bsplit* command should be used after the Pave Filler is filled.

```
# s1 s2 s3 - objects
# t1 t2 t3 - tools
bclearobjects
bcleartools
baddobjects s1 s2 s3
baddtools t1 t2 t3
bfillds
bsplit result
```

9.4 Examples

9.4.1 Example 1

Splitting a face by the set of edges:

```
# draw script for reproducing
bclearobjects
bcleartools

set height 20
cylinder cyl 0 0 0 0 1 10
mkface f cyl 0 2*pi -$height $height
baddobjects f

# create tool edges
compound edges

set nb_uedges 10
set pi2 [dval 2*pi]
set ustep [expr $pi2/$nb_uedges]
for {set i 0} {$i <= $pi2} {set i [expr $i + $ustep]} {
  uiso c cyl $i
  mkedge e c -25 25
  add e edges
}

set nb_vedges 10
set vstep [expr 2*$height/$nb_vedges]
for {set i -20} {$i <= 20} {set i [expr $i + $vstep]} {
  viso c cyl $i
  mkedge e c
  add e edges
}
baddctools edges

bfillds
bsplit result
```




Figure 39: Arguments

9.4.2 Example 2

Splitting a plate by the set of cylinders:

```
# draw script for reproducing:
```

```
bclearobjects
bcleartools

box plate 100 100 1
baddobjects plate

pcylinder p 1 11
compound cylinders
for {set i 0} {$i < 101} {incr i 5} {
  for {set j 0} {$j < 101} {incr j 5} {
    copy p p1;
    ttranslate p1 $i $j -5;
    add p1 cylinders
  }
}
baddtools cylinders

bfillds
bsplit result
```




Figure 41: Arguments

9.4.3 Example 3

Splitting shell hull by the planes:




Figure 43: Arguments

10 Boolean Operations Algorithm

10.1 Arguments

- The arguments of BOA are shapes in terms of *TopoDS_Shape*. The main requirements for the arguments are described in the [Data Structure](#)
- There are two groups of arguments in BOA:
 - Objects ($S1=S11, S12, \dots$);
 - Tools ($S2=S21, S22, \dots$).
- The following table contains the values of dimension for different types of arguments:

No	Type of Argument	Index of Type	Dimension
1	COMPOUND	0	One of 0, 1, 2, 3
2	COMPSOLID	1	3
3	SOLID	2	3
4	SHELL	3	2
5	FACE	4	2
6	WIRE	5	1
7	EDGE	6	1
8	VERTEX	7	0

- For Boolean operation Fuse all arguments should have equal dimensions.
- For Boolean operation Cut the minimal dimension of $S2$ should not be less than the maximal dimension of $S1$.
- For Boolean operation Common the arguments can have any dimension.

10.2 Results. General Rules


- The result of the Boolean operation is a compound (if defined). Each sub-shape of the compound has shared sub-shapes in accordance with interferences between the arguments.
- The content of the result depends on the type of the operation (Common, Fuse, Cut12, Cut21) and the dimensions of the arguments.
- The result of the operation Fuse is defined for arguments $S1$ and $S2$ that have the same dimension value : $Dim(S1)=Dim(S2)$. If the arguments have different dimension values the result of the operation Fuse is not defined. The dimension of the result is equal to the dimension of the arguments. For example, it is impossible to fuse an edge and a face.
- The result of the operation Fuse for arguments $S1$ and $S2$ contains the parts of arguments that have states **OUT** relative to the opposite arguments.
- The result of the operation Fuse for arguments $S1$ and $S2$ having dimension value 3 (Solids) is refined by removing all possible internal faces to provide minimal number of solids.
- The result of the operation Common for arguments $S1$ and $S2$ is defined for all values of the dimensions of the arguments. The result can contain shapes of different dimensions, but the minimal dimension of the result will be equal to the minimal dimension of the arguments. For example, the result of the operation Common between edges cannot be a vertex.
- The result of the operation Common for the arguments $S1$ and $S2$ contains the parts of the argument that have states **IN** and **ON** relative to the opposite argument.

- The result of the operation *Cut* is defined for arguments *S1* and *S2* that have values of dimensions $Dim(\leftrightarrow S2)$ that should not be less than $Dim(S1)$. The result can contain shapes of different dimensions, but the minimal dimension of the result will be equal to the minimal dimension of the objects $Dim(S1)$. The result of the operation *Cut12* is not defined for other cases. For example, it is impossible to cut an edge from a solid, because a solid without an edge is not defined.
- The result of the operation *Cut12* for arguments *S1* and *S2* contains the parts of argument *S1* that have state **OUT** relative to the opposite argument *S2*.
- The result of the operation *Cut21* for arguments *S1* and *S2* contains the parts of argument *S2* that have state **OUT** relative to the opposite argument *S1*.
- For the arguments of collection type (WIRE, SHELL, COMPSOLID) the type will be passed in the result. For example, the result of Common operation between Shell and Wire will be a compound containing Wire.
- For the arguments of collection type (WIRE, SHELL, COMPSOLID) containing overlapping parts the overlapping parts passed into result will be repeated for each container from the input shapes containing such parts. The containers completely included in other containers will be avoided in the result.
- For the arguments of collection type (WIRE, SHELL, COMPSOLID) the containers included into result will have the same orientation as the original containers from arguments. In case of duplication its orientation will be defined by the orientation of the first container in arguments. Each container included into result will have coherent orientation of its sub-shapes.
- The result of the operation *Fuse* for the arguments of collection type (WIRE, SHELL) will consist of the shapes of the same collection type. The overlapping parts (EDGES/FACES) will be shared among containers, but duplicating containers will be avoided in the result. For example, the result of *Fuse* operation between two fully coinciding wires will be one wire, but the result of *Fuse* operation between two partially coinciding wires will be two wires sharing coinciding edges.
- The result of the operation *Fuse* for the arguments of type COMPSOLID will consist of the compound containing COMPSOLIDs created from connexity blocks of fused solids.
- The result of the operation *Common* for the arguments of collection type (WIRE, SHELL, COMPSOLID) will consist of the unique containers containing the overlapping parts. For example, the result of *Common* operation between two fully overlapping wires will be one wire containing all splits of edges. The number of wires in the result of *Common* operation between two partially overlapping wires will be equal to the number of connexity blocks of overlapping edges.


10.3 Examples

10.3.1 Case 1: Two Vertices

Let us consider two interfering vertices *V1* and *V2*:




- The result of *Fuse* operation is the compound that contains new vertex *V*.




- The result of *Common* operation is a compound containing new vertex V .
- The result of *Cut12* operation is an empty compound.
- The result of *Cut21* operation is an empty compound.

10.3.2 Case 2: A Vertex and an Edge

Let us consider vertex V_1 and the edge E_2 , that intersect in a 3D point:




- The result of *Fuse* operation is result is not defined because the dimension of the vertex (0) is not equal to the dimension of the edge (1).
- The result of *Common* operation is a compound containing vertex V_1 as the argument V_1 has a common part with edge E_2 .




- The result of *Cut12* operation is an empty compound.
- The result of *Cut21* operation is not defined because the dimension of the vertex (0) is less than the dimension of the edge (1).

10.3.3 Case 3: A Vertex and a Face

Let us consider vertex V_1 and face F_2 , that intersect in a 3D point:




- The result of *Fuse* operation is not defined because the dimension of the vertex (0) is not equal to the dimension of the face (2).
- The result of *Common* operation is a compound containing vertex V_1 as the argument V_1 has a common part with face F_2 .




- The result of *Cut12* operation is an empty compound.
- The result of *Cut21* operation is not defined because the dimension of the vertex (0) is less than the dimension of the face (2).

10.3.4 Case 4: A Vertex and a Solid

Let us consider vertex V_1 and solid S_2 , that intersect in a 3D point:




- The result of *Fuse* operation is not defined because the dimension of the vertex (0) is not equal to the dimension of the solid (3).
- The result of *Common* operation is a compound containing vertex V_1 as the argument V_1 has a common part with solid S_2 .




- The result of *Cut12* operation is an empty compound.
- The result of *Cut21* operation is not defined because the dimension of the vertex (0) is less than the dimension of the solid (3).

10.3.5 Case 5: Two edges intersecting at one point

Let us consider edges E_1 and E_2 that intersect in a 3D point:




- The result of *Fuse* operation is a compound containing split parts of arguments i.e. 4 new edges E_{11} , E_{12} , E_{21} , and E_{22} . These edges have one shared vertex V_{n1} . In this case:
 - argument edge E_1 has resulting split edges E_{11} and E_{12} (image of E_1);
 - argument edge E_2 has resulting split edges E_{21} and E_{22} (image of E_2).




- The result of *Common* operation is an empty compound because the dimension (0) of the common part between the edges (vertex) is less than the dimension of the arguments (1).
- The result of *Cut12* operation is a compound containing split parts of the argument E_1 , i.e. 2 new edges E_{11} and E_{12} . These edges have one shared vertex V_{n1} .

In this case the argument edge E_1 has resulting split edges E_{11} and E_{12} (image of E_1).




- The result of *Cut21* operation is a compound containing split parts of the argument $E2$, i.e. 2 new edges $E21$ and $E12$. These edges have one shared vertex $Vn1$.

In this case the argument edge $E2$ has resulting split edges $E21$ and $E22$ (image of $E2$).




10.3.6 Case 6: Two edges having a common block


Let us consider edges $E1$ and $E2$ that have a common block:




- The result of *Fuse* operation is a compound containing split parts of arguments i.e. 3 new edges $E11$, $E12$ and $E22$. These edges have two shared vertices. In this case:
 - argument edge $E1$ has resulting split edges $E11$ and $E12$ (image of $E1$);
 - argument edge $E2$ has resulting split edges $E21$ and $E22$ (image of $E2$);
 - edge $E12$ is common for the images of $E1$ and $E2$.




- The result of *Common* operation is a compound containing split parts of arguments i.e. 1 new edge E_{12} . In this case edge E_{12} is common for the images of E_1 and E_2 . The common part between the edges (edge) has the same dimension (1) as the dimension of the arguments (1).



- The result of *Cut12* operation is a compound containing a split part of argument E_1 , i.e. new edge E_{11} .




- The result of *Cut21* operation is a compound containing a split part of argument E_2 , i.e. new edge E_{22} .




10.3.7 Case 7: An Edge and a Face intersecting at a point

Let us consider edge $E1$ and face $F2$ that intersect at a 3D point:



- The result of *Fuse* operation is not defined because the dimension of the edge (1) is not equal to the dimension of the face (2).
- The result of *Common* operation is an empty compound because the dimension (0) of the common part between the edge and face (vertex) is less than the dimension of the arguments (1).
- The result of *Cut12* operation is a compound containing split parts of the argument $E1$, i.e. 2 new edges $E11$ and $E12$.


In this case the argument edge $E1$ has no common parts with the face $F2$ so the whole image of $E1$ is in the result.



- The result of *Cut21* operation is not defined because the dimension of the edge (1) is less than the dimension of the face (2).


10.3.8 Case 8: A Face and an Edge that have a common block

Let us consider edge $E1$ and face $F2$ that have a common block:




- The result of *Fuse* operation is not defined because the dimension of the edge (1) is not equal to the dimension of the face (2).
- The result of *Common* operation is a compound containing a split part of the argument $E1$, i.e. new edge $E12$.

In this case the argument edge $E1$ has a common part with face $F2$ so the corresponding part of the image of $E1$ is in the result. The yellow square is not a part of the result. It only shows the place of $F2$.



- The result of *Cut12* operation is a compound containing split part of the argument $E1$, i.e. new edge $E11$.


In this case the argument edge $E1$ has a common part with face $F2$ so the corresponding part is not included into the result. The yellow square is not a part of the result. It only shows the place of $F2$.



- The result of *Cut21* operation is not defined because the dimension of the edge (1) is less than the dimension of the face (2).


10.3.9 Case 9: An Edge and a Solid intersecting at a point

Let us consider edge $E1$ and solid $S2$ that intersect at a point:




- The result of *Fuse* operation is not defined because the dimension of the edge (1) is not equal to the dimension of the solid (3).
- The result of *Common* operation is a compound containing a split part of the argument $E1$, i.e. new edge $E12$.

In this case the argument edge $E1$ has a common part with solid $S2$ so the corresponding part of the image of $E1$ is in the result. The yellow square is not a part of the result. It only shows the place of $S2$.



- The result of *Cut12* operation is a compound containing split part of the argument $E1$, i.e. new edge $E11$.


In this case the argument edge $E1$ has a common part with solid $S2$ so the corresponding part is not included into the result. The yellow square is not a part of the result. It only shows the place of $S2$.



- The result of *Cut21* operation is not defined because the dimension of the edge (1) is less than the dimension of the solid (3).


10.3.10 Case 10: An Edge and a Solid that have a common block

Let us consider edge $E1$ and solid $S2$ that have a common block:




- The result of *Fuse* operation is not defined because the dimension of the edge (1) is not equal to the dimension of the solid (3).
- The result of *Common* operation is a compound containing a split part of the argument $E1$, i.e. new edge $E12$.

In this case the argument edge $E1$ has a common part with solid $S2$ so the corresponding part of the image of $E1$ is in the result. The yellow square is not a part of the result. It only shows the place of $S2$.



- The result of *Cut12* operation is a compound containing split part of the argument $E1$, i.e. new edge $E11$.


In this case the argument edge $E1$ has a common part with solid $S2$ so the corresponding part is not included into the result. The yellow square is not a part of the result. It only shows the place of $S2$.




- The result of *Cut21* operation is not defined because the dimension of the edge (1) is less than the dimension of the solid (3).

10.3.11 Case 11: Two intersecting faces


Let us consider two intersecting faces $F1$ and $F2$:




- The result of *Fuse* operation is a compound containing split parts of arguments i.e. 2 new faces F_{11} and F_{21} . These faces have one shared edge E_{n1} .



- The result of *Common* operation is an empty compound because the dimension (1) of the common part between F_1 and F_2 (edge) is less than the dimension of arguments (2).
- The result of *Cut12* operation is a compound containing split part of the argument F_1 , i.e. new face F_{11} .




- The result of *Cut21* operation is a compound containing split parts of the argument $F2$, i.e. 1 new face $F21$.




10.3.12 Case 12: Two faces that have a common part


Let us consider two faces $F1$ and $F2$ that have a common part:




- The result of *Fuse* operation is a compound containing split parts of arguments, i.e. 3 new faces: $F11$, $F12$ and $F22$. These faces are shared through edges. In this case:
 - the argument edge $F1$ has resulting split faces $F11$ and $F12$ (image of $F1$)
 - the argument face $F2$ has resulting split faces $F12$ and $F22$ (image of $F2$)
 - the face $F12$ is common for the images of $F1$ and $F2$.




- The result of *Common* operation is a compound containing split parts of arguments i.e. 1 new face F_{12} . In this case: face F_{12} is common for the images of F_1 and F_2 . The common part between the faces (face) has the same dimension (2) as the dimension of the arguments (2).



- The result of *Cut12* operation is a compound containing split part of the argument F_1 , i.e. new face F_{11} .




- The result of *Cut21* operation is a compound containing split parts of the argument F_2 , i.e. 1 new face F_{21} .




10.3.13 Case 13: Two faces that have a common edge


Let us consider two faces F_1 and F_2 that have a common edge:




- The result of *Fuse* operation is a compound containing split parts of arguments, i.e. 2 new faces: F_{11} and F_{21} . These faces have one shared edge E_{n1} .



- The result of *Common* operation is an empty compound because the dimension (1) of the common part between F_1 and F_2 (edge) is less than the dimension of the arguments (2)
- The result of *Cut12* operation is a compound containing split part of the argument F_1 , i.e. new face F_{11} . The vertices are shown just to clarify the fact that the edges are splitted.




- The result of *Cut21* operation is a compound containing split parts of the argument F_2 , i.e. 1 new face F_{21} . The vertices are shown just to clarify the fact that the edges are splitted.




10.3.14 Case 14: Two faces that have a common vertex


Let us consider two faces $F1$ and $F2$ that have a common vertex:




- The result of *Fuse* operation is a compound containing split parts of arguments, i.e. 2 new faces: $F11$ and $F21$. These faces have one shared vertex $Vn1$.



- The result of *Common* operation is an empty compound because the dimension (0) of the common part between $F1$ and $F2$ (vertex) is less than the dimension of the arguments (2)
- The result of *Cut12* operation is a compound containing split part of the argument $F1$, i.e. new face $F11$.




- The result of *Cut21* operation is a compound containing split parts of the argument $F2$, i.e. 1 new face $F21$.




10.3.15 Case 15: A Face and a Solid that have an intersection curve.


Let us consider face $F1$ and solid $S2$ that have an intersection curve:



- The result of *Fuse* operation is not defined because the dimension of the face (2) is not equal to the dimension of the solid (3).
- The result of *Common* operation is a compound containing split part of the argument $F1$. In this case the argument face $F1$ has a common part with solid $S2$, so the corresponding part of the image of $F1$ is in the result. The yellow contour is not a part of the result. It only shows the place of $S2$.




- The result of *Cut12* operation is a compound containing split part of the argument *F1*. In this case argument face *F1* has a common part with solid *S2* so the corresponding part is not included into the result. The yellow contour is not a part of the result. It only shows the place of *S2*.




- The result of *Cut21* operation is not defined because the dimension of the face (2) is less than the dimension of the solid (3).

10.3.16 Case 16: A Face and a Solid that have overlapping faces.


Let us consider face *F1* and solid *S2* that have overlapping faces:



- The result of *Fuse* operation is not defined because the dimension of the face (2) is not equal to the dimension of the solid (3).
- The result of *Common* operation is a compound containing split part of the argument *F1*. In this case the argument face *F1* has a common part with solid *S2*, so the corresponding part of the image of *F1* is included in the result. The yellow contour is not a part of the result. It only shows the place of *S2*.




- The result of *Cut12* operation is a compound containing split part of the argument *F1*. In this case argument face *F1* has a common part with solid *S2* so the corresponding part is not included into the result. The yellow contour is not a part of the result. It only shows the place of *S2*.




- The result of *Cut21* operation is not defined because the dimension of the face (2) is less than the dimension of the solid (3).

10.3.17 Case 17: A Face and a Solid that have overlapping edges.

Let us consider face $F1$ and solid $S2$ that have overlapping edges:




- The result of *Fuse* operation is not defined because the dimension of the face (2) is not equal to the dimension of the solid (3).
- The result of *Common* operation is an empty compound because the dimension (1) of the common part between $F1$ and $S2$ (edge) is less than the lower dimension of the arguments (2).
- The result of *Cut12* operation is a compound containing split part of the argument $F1$. In this case argument face $F1$ has a common part with solid $S2$ so the corresponding part is not included into the result. The yellow contour is not a part of the result. It only shows the place of $S2$.




- The result of *Cut11* operation is not defined because the dimension of the face (2) is less than the dimension of the solid (3).

10.3.18 Case 18: A Face and a Solid that have overlapping vertices.

Let us consider face $F1$ and solid $S2$ that have overlapping vertices:




- The result of *Fuse* operation is not defined because the dimension of the face (2) is not equal to the dimension of the solid (3).
- The result of *Common* operation is an empty compound because the dimension (1) of the common part between $F1$ and $S2$ (vertex) is less than the lower dimension of the arguments (2).
- The result of *Cut12* operation is a compound containing split part of the argument $F1$. In this case argument face $F1$ has a common part with solid $S2$ so the corresponding part is not included into the result. The yellow contour is not a part of the result. It only shows the place of $S2$.




- The result of *Cut21* operation is not defined because the dimension of the face (2) is less than the dimension of the solid (3).

10.3.19 Case 19: Two intersecting Solids.


Let us consider two intersecting solids $S1$ and $S2$:




- The result of *Fuse* operation is a compound composed from the split parts of arguments $S11$, $S12$ and $S22$ (*Cut12*, *Common*, *Cut21*). All inner webs are removed, so the result is one new solid R .




- The result of *Common* operation is a compound containing split parts of arguments i.e. one new solid S_{12} . In this case solid S_{12} is common for the images of S_1 and S_2 . The common part between the solids (solid) has the same dimension (3) as the dimension of the arguments (3). The yellow contour is not a part of the result. It only shows the place of S_1 .



- The result of *Cut12* operation is a compound containing split part of the argument S_1 , i.e. 1 new solid S_{11} .




- The result of *Cut21* operation is a compound containing split part of the argument S_2 , i.e. 1 new solid S_{21} .




10.3.20 Case 20: Two Solids that have overlapping faces.


Let us consider two solids $S1$ and $S2$ that have a common part on face:




- The result of *Fuse* operation is a compound composed from the split parts of arguments $S11$, $S12$ and $S22$ (*Cut12*, *Common*, *Cut21*). All inner webs are removed, so the result is one new solid R .



- The result of *Common* operation is an empty compound because the dimension (2) of the common part between $S1$ and $S2$ (face) is less than the lower dimension of the arguments (3).
- The result of *Cut12* operation is a compound containing split part of the argument $S1$, i.e. 1 new solid $S11$.




- The result of *Cut21* operation is a compound containing split part of the argument $S2$, i.e. 1 new solid $S21$.




10.3.21 Case 21: Two Solids that have overlapping edges.


Let us consider two solids S_1 and S_2 that have overlapping edges:




- The result of *Fuse* operation is a compound composed from the split parts of arguments i.e. 2 new solids S_{11} and S_{21} . These solids have one shared edge E_{n1} .



- The result of *Common* operation is an empty compound because the dimension (1) of the common part between S_1 and S_2 (edge) is less than the lower dimension of the arguments (3).
- The result of *Cut12* operation is a compound containing split part of the argument S_1 . In this case argument S_1 has a common part with solid S_2 so the corresponding part is not included into the result.




- The result of *Cut21* operation is a compound containing split part of the argument *S2*. In this case argument *S2* has a common part with solid *S1* so the corresponding part is not included into the result.




10.3.22 Case 22: Two Solids that have overlapping vertices.


Let us consider two solids *S1* and *S2* that have overlapping vertices:




- The result of *Fuse* operation is a compound composed from the split parts of arguments i.e. 2 new solids S_{11} and S_{21} . These solids share V_{n1} .



- The result of *Common* operation is an empty compound because the dimension (0) of the common part between S_1 and S_2 (vertex) is less than the lower dimension of the arguments (3).
- The result of *Cut12* operation is a compound containing split part of the argument S_1 .




- The result of *Cut21* operation is a compound containing split part of the argument S_2 .




10.3.23 Case 23: A Shell and a Wire cut by a Solid.


Let us consider Shell Sh and Wire W as the objects and Solid S as the tool:



- The result of *Fuse* operation is not defined as the dimension of the arguments is not the same.
- The result of *Common* operation is a compound containing the parts of the initial Shell and Wire common for the Solid. The new Shell and Wire are created from the objects.




- The result of *Cut12* operation is a compound containing new Shell and Wire split from the arguments *Sh* and *W*. In this case they have a common part with solid *S* so the corresponding part is not included into the result.




- The result of *Cut21* operation is not defined as the objects have a lower dimension than the tool.

10.3.24 Case 24: Two Wires that have overlapping edges.


Let us consider two Wires that have overlapping edges, *W1* is the object and *W2* is the tool:




- The result of *Fuse* operation is a compound containing two Wires, which share an overlapping edge. The new Wires are created from the objects:




- The result of *Common* operation is a compound containing one Wire consisting of an overlapping edge. The new Wire is created from the objects:



- The result of *Cut12* operation is a compound containing a wire split from object *W1*. Its common part with *W2* is not included into the result.



- The result of *Cut21* operation is a compound containing a wire split from *W2*. Its common part with *W1* is not included into the result.



10.4 Class BOPAlgo_BOP

BOA is implemented in the class *BOPAlgo_BOP*. The main fields of this class are described in the Table:

Name	Contents
<i>myOperation</i>	The type of the Boolean operation (Common, Fuse, Cut)
<i>myTools</i>	The tools
<i>myDims[2]</i>	The values of the dimensions of the arguments
<i>myRC</i>	The draft result (shape)

The main steps of the *BOPAlgo_BOP* are the same as of *BOPAlgo_Builder* except for some aspects described in the next paragraphs.

10.5 Building Draft Result

The input data for this step is as follows:

- *BOPAlgo_BOP* object after building result of type *Compound*;
- *Type* of the Boolean operation.

No	Contents	Implementation
1	For the Boolean operation <i>Fuse</i> add to <i>myRC</i> all images of arguments.	<i>BOPAlgo_BOP::BuildRC()</i>
2	For the Boolean operation <i>Common</i> or <i>Cut</i> add to <i>myRC</i> all images of argument <i>S1</i> that are <i>Common</i> for the Common operation and are <i>Not Common</i> for the Cut operation	<i>BOPAlgo_BOP::BuildRC()</i>

10.6 Building the Result

The input data for this step is as follows:

- *BOPAlgo_BOP* object the state after building draft result.

No	Contents	Implementation
1	For the Type of the Boolean operation Common, Cut with any dimension and operation Fuse with $myDim[0] < 3$	
1.↔ 1	Find containers (WIRE, SHELL, COMPSOLID) in the arguments	<i>BOPAlgo_BOP::BuildShape()</i>
1.↔ 2	Make connexity blocks from splits of each container that are in <i>myRC</i>	<i>BOPTools_Tools::MakeConnexityBlocks()</i>
1.↔ 3	Build the result from shapes made from the connexity blocks	<i>BOPAlgo_BOP::BuildShape()</i>
1.↔ 4	Add the remaining shapes from <i>myRC</i> to the result	<i>BOPAlgo_BOP::BuildShape()</i>
2	For the Type of the Boolean operation Fuse with $myDim[0] = 3$	
2.↔ 1	Find internal faces (<i>FWi</i>) in <i>myRC</i>	<i>BOPAlgo_BOP::BuildSolid()</i>
2.↔ 2	Collect all faces of <i>myRC</i> except for internal faces (<i>FWi</i>) -> <i>SFS</i>	<i>BOPAlgo_BOP::BuildSolid ()</i>
2.↔ 3	Build solids (<i>SDi</i>) from <i>SFS</i> .	<i>BOPAlgo_BuilderSolid</i>
2.↔ 4	Add the solids (<i>SDi</i>) to the result	

11 Section Algorithm

11.1 Arguments

The arguments of BOA are shapes in terms of *TopoDS_Shape*. The main requirements for the arguments are described in the Algorithms.


11.2 Results and general rules

- The result of Section operation is a compound. Each sub-shape of the compound has shared sub-shapes in accordance with interferences between the arguments.
- The result of Section operation contains shapes that have dimension that is less than 2 i.e. vertices and edges.
- The result of Section operation contains standalone vertices if these vertices do not belong to the edges of the result.
- The result of Section operation contains vertices and edges of the arguments (or images of the arguments) that belong to at least two arguments (or two images of the arguments).
- The result of Section operation contains Section vertices and edges obtained from Face/Face interferences.
- The result of Section operation contains vertices that are the result of interferences between vertices and faces.
- The result of Section operation contains edges that are the result of interferences between edges and faces (Common Blocks),


11.3 Examples

11.3.1 Case 1: Two Vertices

Let us consider two interfering vertices: V_1 and V_2 .




The result of *Section* operation is the compound that contains a new vertex V .




11.3.2 Case 1: Case 2: A Vertex and an Edge

Let us consider vertex V_1 and the edge E_2 , that intersect in a 3D point:




The result of *Section* operation is the compound that contains vertex V_1 .




11.3.3 Case 1: Case 2: A Vertex and a Face

Let us consider vertex V_1 and face F_2 , that intersect in a 3D point:




The result of *Section* operation is the compound that contains vertex V_1 .



11.3.4 Case 4: A Vertex and a Solid


Let us consider vertex $V1$ and solid $Z2$. The vertex $V1$ is inside the solid $Z2$.




The result of *Section* operation is an empty compound.

11.3.5 Case 5: Two edges intersecting at one point

Let us consider edges $E1$ and $E2$, that intersect in a 3D point:




The result of *Section* operation is the compound that contains a new vertex V_{new} .




11.3.6 Case 6: Two edges having a common block

Let us consider edges E_1 and E_2 , that have a common block:




The result of *Section* operation is the compound that contains a new edge E_{new} .



11.3.7 Case 7: An Edge and a Face intersecting at a point

Let us consider edge E_1 and face F_2 , that intersect at a 3D point:




The result of *Section* operation is the compound that contains a new vertex V_{new} .




11.3.8 Case 8: A Face and an Edge that have a common block

Let us consider edge E_1 and face F_2 , that have a common block:




The result of *Section* operation is the compound that contains new edge E_{new} .




11.3.9 Case 9: An Edge and a Solid intersecting at a point

Let us consider edge $E1$ and solid $Z2$, that intersect at a point:




The result of *Section* operation is the compound that contains a new vertex V_{new} .



11.3.10 Case 10: An Edge and a Solid that have a common block

Let us consider edge $E1$ and solid $Z2$, that have a common block at a face:




The result of *Section* operation is the compound that contains a new edge E_{new} .




11.3.11 Case 11: Two intersecting faces

Let us consider two intersecting faces F_1 and F_2 :




The result of *Section* operation is the compound that contains a new edge E_{new} .




11.3.12 Case 12: Two faces that have a common part

Let us consider two faces F_1 and F_2 that have a common part:




The result of *Section* operation is the compound that contains 4 new edges.




11.3.13 Case 13: Two faces that have overlapping edges

Let us consider two faces F_1 and F_2 that have a overlapping edges:




The result of *Section* operation is the compound that contains a new edge E_{new} .




11.3.14 Case 14: Two faces that have overlapping vertices

Let us consider two faces F_1 and F_2 that have overlapping vertices:




The result of *Section* operation is the compound that contains a new vertex V_{new} .




11.3.15 Case 15: A Face and a Solid that have an intersection curve

Let us consider face F_1 and solid Z_2 that have an intersection curve:




The result of *Section* operation is the compound that contains new edges.




11.3.16 Case 16: A Face and a Solid that have overlapping faces.

Let us consider face F_1 and solid Z_2 that have overlapping faces:




The result of *Section* operation is the compound that contains new edges




11.3.17 Case 17: A Face and a Solid that have overlapping edges.

Let us consider face F_1 and solid Z_2 that have a common part on edge:




The result of *Section* operation is the compound that contains a new edge E_{new} .




11.3.18 Case 18: A Face and a Solid that have overlapping vertices.

Let us consider face F_1 and solid Z_2 that have overlapping vertices:




The result of *Section* operation is the compound that contains a new vertex V_{new} .




11.3.19 Case 19: Two intersecting Solids

Let us consider two intersecting solids Z_1 and Z_2 :




The result of *Section* operation is the compound that contains new edges.




11.3.20 Case 20: Two Solids that have overlapping faces

Let us consider two solids Z_1 and Z_2 that have a common part on face:




The result of *Section* operation is the compound that contains new edges.




11.3.21 Case 21: Two Solids that have overlapping edges

Let us consider two solids Z_1 and Z_2 that have overlapping edges:




The result of *Section* operation is the compound that contains a new edge E_{new} .




11.3.22 Case 22: Two Solids that have overlapping vertices

Let us consider two solids Z_1 and Z_2 that have overlapping vertices:



The result of *Section* operation is the compound that contains a new vertex *Vnew*.



11.4 Class BOPAlgo_Section

SA is implemented in the class *BOPAlgo_Section*. The class has no specific fields. The main steps of the *BOPAlgo_Section* are the same as of *BOPAlgo_Builder* except for the following steps:

- Build Images for Wires;
- Build Result of Type Wire;
- Build Images for Faces;
- Build Result of Type Face;
- Build Images for Shells;
- Build Result of Type Shell;
- Build Images for Solids;
- Build Result of Type Solid;
- Build Images for Type CompSolid;
- Build Result of Type CompSolid;
- Build Images for Compounds; Some aspects of building the result are described in the next paragraph

11.5 Building the Result

No	Contents	Implementation
1	Build the result of the operation using all information contained in <i>FaceInfo</i> , Common Block, Shared entities of the arguments, etc.	<i>BOPAlgo_Section::BuildSection()</i>

12 Volume Maker Algorithm

The Volume Maker algorithm has been designed for building the elementary volumes (solids) from a set of connected, intersecting, or nested shapes. The algorithm can also be useful for splitting solids into parts, or constructing new solid(s) from set of intersecting or connected faces or shells. The algorithm creates only closed solids. In general case the result solids are non-manifold: fragments of the input shapes (wires, faces) located inside the solids are added as internal sub-shapes to these solids. But the algorithm allows preventing the addition of the internal for solids parts into result. In this case the result solids will be manifold and not contain any internal parts. However, this option does not prevent from the occurrence of the internal edges or vertices in the faces.

Non-closed faces, free wires etc. located outside of any solid are always excluded from the result.

The Volume Maker algorithm is implemented in the class `BOPAlgo_MakerVolume`. It is based on the General Fuse (GF) algorithm. All the options of the GF algorithm (see [GF Options](#)) are also available in this algorithm.

The requirements for the arguments are the same as for the arguments of GF algorithm - they could be of any type, but each argument should be valid and not self-interfered.

The algorithm allows disabling the calculation of intersections among the arguments. In this case the algorithm will run much faster, but the user should guarantee that the arguments do not interfere with each other, otherwise the result will be invalid (e.g. contain unexpected parts) or empty. This option is useful e.g. for building a solid from the faces of one shell or from the shapes that have already been intersected.

12.1 Usage

C++ Level

The usage of the algorithm on the API level:

```
BOPAlgo_MakerVolume aMV;
// Set the arguments
TopTools_ListOfShape aLS = ...; // arguments
aMV.SetArguments(aLS);

// Set options for the algorithm
// setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
// chapter)
...
// Additional option of the algorithm
Standard_Boolean bAvoidInternalShapes = Standard_False; // Set to True to exclude from the result any
// shapes internal to the solids
aMV.SetAvoidInternalShapes(bAvoidInternalShapes);

// Perform the operation
aMV.Perform();
if (aMV.HasErrors()) { //check error status
    return;
}
//
const TopoDS_Shape& aResult = aMV.Shape(); // result of the operation
```

Tcl Level

To use the algorithm in Draw the command `mkvolume` has been implemented. The usage of this command is following:

```
Usage: mkvolume r b1 b2 ... [-c] [-ni] [-ai]
Options:
-c - use this option to have input compounds considered as set of separate arguments (allows passing
    multiple arguments as one compound);
-ni - use this option to disable the intersection of the arguments;
-ai - use this option to avoid internal for solids shapes in the result.
```

12.2 Examples

Example 1

Creation of 9832 solids from sphere and set of 63 planes:




Figure 45: Arguments

Example 2

Creating compartments on a ship defined by hull shell and a set of planes. The ship is divided on compartments by five transverse bulkheads and a deck – six compartments are created:




Figure 47: Arguments

13 Cells Builder algorithm

The Cells Builder algorithm is an extension of the General Fuse algorithm. The result of General Fuse algorithm contains all split parts of the arguments. The Cells Builder algorithm provides means to specify if any given split part of the arguments (referred to as Cell) can be taken or avoided in the result.

The possibility of selecting any Cell allows combining any possible result and gives the Cells Builder algorithm a very wide sphere of application - from building the result of any Boolean operation to building the result of any application-specific operation.

The algorithm builds Cells only once and then just reuses them for combining the result. This gives this algorithm the performance advantage over Boolean operations, which always rebuild the splits to obtain the desirable result.

Thus, the Cells Builder algorithm can be especially useful for simulating Boolean expressions, i.e. a sequence of Boolean operations on the same arguments. Instead of performing many Boolean operations it allows getting the final result in a single operation. The Cells Builder will also be beneficial to obtain the results of different Boolean operations on the same arguments - Cut and Common, for example.

The Cells Builder algorithm also provides the possibility to remove any internal boundaries between splits of the same type, i.e. to fuse any same-dimensional parts added into the result and to keep any other parts as separate. This possibility is implemented through the Cells material approach: to remove the boundary between two Cells, both Cells should be assigned with the same material ID. However, if the same material ID has been assigned to the Cells of different dimension, the removal of the internal boundaries for that material will not be performed. Currently, such case is considered a limitation for the algorithm.

The algorithm can also create containers from the connected Cells added into result - WIRES from Edges, SHELLS from Faces and COMPSOLIDS from Solids.

13.1 Usage

The algorithm has been implemented in the *BOPAlgo_CellsBuilder* class.

Cells Builder is based on the General Fuse algorithm. Thus all options of the General Fuse algorithm (see [GF Options](#)) are also available in this algorithm.

The requirements for the input shapes are the same as for General Fuse - each argument should be valid in terms of *BRepCheck_Analyzer* and *BOPAlgo_ArgumentAnalyzer*.

The result of the algorithm is a compound containing the selected parts of the basic type (VERTEX, EDGE, FACE or SOLID). The default result is an empty compound. It is possible to add any Cell by using the methods *AddToResult()* and *AddAllToResult()*. It is also possible to remove any part from the result by using methods *RemoveFromResult()* and *RemoveAllFromResult()*. The method *RemoveAllFromResult()* is also suitable for clearing the result.

The Cells that should be added/removed to/from the result are defined through the input shapes containing the parts that should be taken **(ShapesToTake)** and the ones containing parts that should be avoided (*ShapesToAvoid*). To be taken into the result the part must be IN all shapes from *ShapesToTake* and OUT of all shapes from *ShapesToAvoid*.

To remove Internal boundaries, it is necessary to set the same material to the Cells, between which the boundaries should be removed, and call the method *RemoveInternalBoundaries()*. The material should not be equal to 0, as this is the default material ID. The boundaries between Cells with this material ID will not be removed. The same Cell cannot be added with different materials. It is also possible to remove the boundaries when the result is combined. To do this, it is necessary to set the material for parts (not equal to 0) and set the flag *bUpdate* to TRUE. If the same material ID has been set for parts of different dimension, the removal of internal boundaries for this material will not be performed.

It is possible to create typed Containers from the parts added into result by using method *MakeContainers()*. The type of the containers will depend on the type of the input shapes: WIRES for EDGE, SHELLS for FACES and COMPSOLIDS for SOLIDS. The result will be a compound containing containers.

API usage

Here is the example of the algorithm use on the API level:

```
BOPAlgo_CellsBuilder aCBuilder;
// Set the arguments
TopTools_ListOfShape aLS = ...; // arguments
aCBuilder.SetArguments(aLS);

// Set options for the algorithm
// setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
// chapter)
...

aCBuilder.Perform(); // build splits of all arguments (GF)
if (aCBuilder.HasErrors()) { // check error status
    return;
}
//
// collecting of the cells into result
const TopoDS_Shape& anEmptyRes = aCBuilder.Shape(); // empty result, as nothing has been added yet
const TopoDS_Shape& anAllCells = aCBuilder.GetAllParts(); //all split parts
//
TopTools_ListOfShape aLSToTake = ...; // parts of these arguments will be taken into result
TopTools_ListOfShape aLSToAvoid = ...; // parts of these arguments will not be taken into result
//
Standard_Integer iMaterial = 1; // defines the material for the cells
Standard_Boolean bUpdate = Standard_False; // defines whether to update the result right now or not
// adding to result
aCBuilder.AddToResult(aLSToTake, aLSToAvoid, iMaterial, bUpdate);
aCBuilder.RemoveInternalBoundaries(); // removing of the boundaries
TopoDS_Shape aResult = aCBuilder.Shape(); // the result
// removing from result
aCBuilder.AddAllToResult();
aCBuilder.RemoveFromResult(aLSToTake, aLSToAvoid);
aResult = aCBuilder.Shape(); // the result
```

DRAW usage

The following set of new commands has been implemented to run the algorithm in DRAW Test Harness:

```
bcbuild      : Initialization of the Cells Builder. Use: *bcbuild r*
bcadd       : Add parts to result. Use: *bcadd r s1 (0,1) s2 (0,1) ... [-m material [-u]]*
bcaddall    : Add all parts to result. Use: *bcaddall r [-m material [-u]]*
bcremove    : Remove parts from result. Use: *bcremove r s1 (0,1) s2 (0,1) ...*
bcremoveall : Remove all parts from result. Use: *bcremoveall*
bcremoveint : Remove internal boundaries. Use: *bcremoveint r*
bcmakecontainers : Make containers from the parts added to result. Use: *bcmakecontainers r*
```

Here is the example of the algorithm use on the DRAW level:

```
psphere s1 15
psphere s2 15
psphere s3 15
ttranslate s1 0 0 10
ttranslate s2 20 0 10
ttranslate s3 10 0 0
bclearobjects; bcleartools
baddobjects s1 s2 s3
bfills
# rx will contain all split parts
bcbuild rx
# add to result the part that is common for all three spheres
bcadd res s1 1 s2 1 s3 1 -m 1
# add to result the part that is common only for first and third spheres
bcadd res s1 1 s2 0 s3 1 -m 1
# remove internal boundaries
bcremoveint res
```

13.2 Examples

The following simple example illustrates the possibilities of the algorithm working on a cylinder and a sphere intersected by a plane:

```
pcylinder c 10 30
```

```
psphere s 15  
ttranslate s 0 0 30  
plane p 0 0 20 1 0 0  
mkface f p -25 30 -17 17
```




Figure 49: Arguments

```
bclearobjects  
bcleartools  
baddobjects c s f  
bfillds  
bcbuild r
```

1. Common for all arguments

```
bcremoveall  
bcadd res c 1 s 1 f 1
```



Figure 50: The result of COMMON operation

2. Common between cylinder and face

```
bcremoveall  
bcadd res f 1 c 1
```



Figure 51: The result of COMMON operation between cylinder and face

3. Common between cylinder and sphere

```
bcremoveall  
bcadd res c 1 s 1
```




Figure 52: The result of COMMON operation between cylinder and sphere

4. Fuse of cylinder and sphere

```
bcremoveall  
bcadd res c 1 -m 1  
bcadd res s 1 -m 1  
bcremoveint res
```




Figure 53: The result of FUSE operation between cylinder and sphere

5. Parts of the face inside solids - FUSE(COMMON(f, c), COMMON(f, s))

```
bcremoveall  
bcadd res f 1 s 1 -m 1  
bcadd res f 1 c 1 -m 1
```




Figure 54: Parts of the face inside solids

```
bcremoveint res
```



Figure 55: Unified parts of the face inside solids

6. Part of the face outside solids

```
bcremoveall  
bcadd res f 1 c 0 s 0
```



Figure 56: Part of the face outside solids

7. Fuse operation (impossible using standard Boolean Fuse operation)

```
bcremoveall  
bcadd res c 1 -m 1  
bcadd res s 1 -m 1  
bcadd res f 1 c 0 s 0  
bcremoveint res
```




Figure 57: Fuse operation

These examples may last forever. To define any new operation, it is just necessary to define, which Cells should be taken and which should be avoided.

14 Algorithm Limitations

The chapter describes the problems that are considered as Algorithm limitations. In most cases an Algorithm failure is caused by a combination of various factors, such as self-interfered arguments, inappropriate or ungrounded values of the argument tolerances, adverse mutual position of the arguments, tangency, etc.

A lot of failures of GFA algorithm can be caused by bugs in low-level algorithms: Intersection Algorithm, Projection Algorithm, Approximation Algorithm, Classification Algorithm, etc.

- The Intersection, Projection and Approximation Algorithms are mostly used at the Intersection step. Their bugs directly cause wrong section results (i.e. incorrect section edges, section points, missing section edges or micro edges). It is not possible to obtain a correct final result of the GFA if a section result is wrong.
- The Projection Algorithm is used at the Intersection step. The purpose of Projection Algorithm is to compute 2D curves on surfaces. Wrong results here lead to incorrect or missing faces in the final GFA result.
- The Classification Algorithm is used at the Building step. The bugs in the Classification Algorithm lead to errors in selecting shape parts (edges, faces, solids) and ultimately to a wrong final GFA result.

The description below illustrates some known GFA limitations. It does not enumerate exhaustively all problems that can arise in practice. Please, address cases of Algorithm failure to the OCCT Maintenance Service.

14.1 Arguments

14.1.1 Common requirements

Each argument should be valid (in terms of *BRepCheck_Analyzer*), or conversely, if the argument is considered as non-valid (in terms of *BRepCheck_Analyzer*), it cannot be used as an argument of the algorithm.

The class *BRepCheck_Analyzer* is used to check the overall validity of a shape. In OCCT a Shape (or its sub-shapes) is considered valid if it meets certain criteria. If the shape is found as invalid, it can be fixed by tools from *ShapeAnalysis*, *ShapeUpgrade* and *ShapeFix* packages.

However, it is important to note that class *BRepCheck_Analyzer* is just a tool that can have its own problems; this means that due to a specific factor(s) this tool can sometimes provide a wrong result.

Let us consider the following example:

The Analyzer checks distances between couples of 3D check-points (P_i , PS_i) of edge E on face F . Point P_i is obtained from the 3D curve (at the parameter t_i) of the edge. PS_i is obtained from 2D curve (at the parameter t_i) of the edge on surface S of face F . To be valid the distance should be less than $Tol(E)$ for all couples of check-points. The number of these check-points is a predefined value (e.g. 23).

Let us consider the case when edge E is recognized valid (in terms of *BRepCheck_Analyzer*).

Further, after some operation, edge E is split into two edges $E1$ and $E2$. Each split edge has the same 3D curve and 2D curve as the original edge E .

Let us check $E1$ (or $E2$). The Analyzer again checks the distances between the couples of check-points points (P_i , PS_i). The number of these check-points is the same constant value (23), but there is no guarantee that the distances will be less than $Tol(E)$, because the points chosen for $E1$ are not the same as for E .

Thus, if $E1$ is recognized by the Analyzer as non-valid, edge E should also be non-valid. However E has been recognized as valid. Thus the Analyzer gives a wrong result for E .

The fact that the argument is a valid shape (in terms of *BRepCheck_Analyzer*) is a necessary but insufficient requirement to produce a valid result of the Algorithms.

14.1.2 Pure self-interference

The argument should not be self-interfered, i.e. all sub-shapes of the argument that have geometrical coincidence through any topological entities (vertices, edges, faces) should share these entities.

Example 1: Compound of two edges

The compound of two edges E_1 and E_2 is a self-interfered shape and cannot be used as the argument of the Algorithms.




Figure 58: Compound of two edges

Example 2: Self-interfered Edge

The edge E is a self-interfered shape and cannot be used as an argument of the Algorithms.




Figure 59: Self-interfered Edge

Example 3: Self-interfered Face

The face F is a self-interfered shape and cannot be used as an argument of the Algorithms.




Figure 60: Self-interfered Face

Example 4: Face of Revolution

The face F has been obtained by revolution of edge E around line L .




Figure 61: Face of Revolution: Arguments




Figure 62: Face of Revolution: Result

In spite of the fact that face F is valid (in terms of *BRepCheck_Analyzer*) it is a self-interfered shape and cannot be used as the argument of the Algorithms.

14.1.3 Self-interferences due to tolerances

Example 1: Non-closed Edge

Let us consider edge E based on a non-closed circle.




Figure 63: Edge based on a non-closed circle

The distance between the vertices of E is $D=0.69799$. The values of the tolerances $Tol(V1)=Tol(V2)=0.5$.




Figure 64: Distance and Tolerances

In spite of the fact that the edge E is valid in terms of *BRepCheck_Analyzer*, it is a self-interfered shape because its vertices are interfered. Thus, edge E cannot be used as an argument of the Algorithms.

Example 2: Solid containing an interfered vertex

Let us consider solid S containing vertex V .




Figure 65: Solid containing an interfered vertex

The value of tolerance $Tol(V) = 50.000075982061$.




Figure 66: Tolerance

In spite of the fact that solid S is valid in terms of *BRepCheck_Analyzer* it is a self-interfered shape because vertex V is interfered with a lot of sub-shapes from S without any topological connection with them. Thus solid S cannot be used as an argument of the Algorithms.

14.1.4 Parametric representation

The parameterization of some surfaces (cylinder, cone, surface of revolution) can be the cause of limitation.

Example 1: Cylindrical surface

The parameterization range for cylindrical surface is:

$$U: [0, 2\pi], V: [-\infty, +\infty]$$

The range of U coordinate is always restricted while the range of V coordinate is non-restricted.

Let us consider a cylinder-based *Face 1* with radii $R=3$ and $H=6$.




Figure 67: Face 1




Figure 68: P-Curves for Face 1

Let us also consider a cylinder-based *Face 2* with radii $R=3000$ and $H=6000$ (resulting from scaling *Face 1* with scale factor $ScF=1000$).




Figure 69: Face 2




Figure 70: P-Curves for Face 2

Please, pay attention to the Zoom value of the Figures.

It is obvious that starting with some value of ScF , e.g. $ScF > 1000000$, all sloped p-Curves on *Face 2* will be almost vertical. At least, there will be no difference between the values of angles computed by standard C Run-Time Library functions, such as `double acos(double x)`. The loss of accuracy in computation of angles can cause failure of some BP sub-algorithms, such as building faces from a set of edges or building solids from a set of faces.

14.1.5 Using tolerances of vertices to fix gaps

It is possible to create shapes that use sub-shapes of lower order to avoid gaps in the tolerance-based data model. Let us consider the following example:




Figure 71: Example

- Face F has two edges $E1$ and $E2$ and two vertices, the base plane is $\{0,0,0, 0,0,1\}$;
- Edge $E1$ is based on line $\{0,0,0, 1,0,0\}$, $Tol(E1) = 1.e-7$;
- Edge $E2$ is based on line $\{0,1,0, 1,0,0\}$, $Tol(E2) = 1.e-7$;
- Vertex $V1$, point $\{0,0.5,0\}$, $Tol(V1) = 1$;
- Vertex $V2$, point $\{10,0.5,0\}$, $Tol(V2) = 1$;
- Face F is valid (in terms of *BRepCheck_Analyzer*).

The values of tolerances $Tol(V1)$ and $Tol(V2)$ are big enough to fix the gaps between the ends of the edges, but the vertices $V1$ and $V2$ do not contain any information about the trajectories connecting the corresponding ends of the edges. Thus, the trajectories are undefined. This will cause failure of some sub-algorithms of BP. For example, the sub-algorithms for building faces from a set of edges use the information about all edges connected in a vertex. The situation when a vertex has several pairs of edges such as above will not be solved in a right way.

14.2 Intersection problems

14.2.1 Pure intersections and common zones

Example: Intersecting Edges

Let us consider the intersection between two edges:

- $E1$ is based on a line: $\{0,-10,0, 1,0,0\}$, $Tol(E1)=2$.
- $E2$ is based on a circle: $\{0,0,0, 0,0,1\}$, $R=10$, $Tol(E2)=2$.




Figure 72: Intersecting Edges

The result of pure intersection between E_1 and E_2 is vertex $V_x \{0, -10, 0\}$.

The result of intersection taking into account tolerances is the common zone CZ (part of 3D-space where the distance between the curves is less than or equals to the sum of edge tolerances).

The Intersection Part of Algorithms uses the result of pure intersection V_x instead of CZ for the following reasons:

- The Algorithms do not produce Common Blocks between edges based on underlying curves of explicitly different type (e.g. Line / Circle). If the curves have different types, the rule of thumb is that the produced result is of type **vertex**. This rule does not work for non-analytic curves (Bezier, B-Spline) and their combinations with analytic curves.
- The algorithm of intersection between two surfaces *IntPatch_Intersection* does not compute CZ of the intersection between curves and points. So even if CZ were computed by Edge/Edge intersection algorithm, its result could not be treated by Face/Face intersection algorithm.

14.2.2 Tolerances and inaccuracies

The following limitations result from modeling errors or inaccuracies.

Example: Intersection of planar faces

Let us consider two planar rectangular faces F_1 and F_2 .

The intersection curve between the planes is curve C_{12} . The curve produces a new intersection edge EC_{12} . The edge goes through vertices V_1 and V_2 thanks to big tolerance values of vertices $Tol(V_1)$ and $Tol(V_2)$. So, two straight edges E_{12} and EC_{12} go through two vertices, which is impossible in this case.




Figure 73: Intersecting Faces

The problem cannot be solved in general, because the length of E_{12} can be infinite and the values of $Tol(V_1)$ and $Tol(V_2)$ theoretically can be infinite too.

In a particular case the problem can be solved in several ways:

- Reduce, if possible, the values of $Tol(V_1)$ and $Tol(V_2)$ (refinement of F_1).
- Analyze the value of $Tol(EC_{12})$ and increase $Tol(EC_{12})$ to get a common part between the edges EC_{12} and E_{12} . Then the common part will be rejected as there is an already existing edge E_{12} for face F_1 .

It is easy to see that if C_{12} is slightly above the tolerance spheres of V_1 and V_2 the problem does not appear.

Example: Intersection of two edges

Let us consider two edges E_1 and E_2 , which have common vertices V_1 and V_2 . The edges E_1 and E_2 have 3D-curves C_1 and C_2 . $Tol(E_1)=1.e^{-7}$, $Tol(E_2)=1.e^{-7}$.

C_1 practically coincides in 3D with C_2 . The value of deflection is $Dmax$ (e.g. $Dmax=1.e^{-6}$).




Figure 74: Intersecting Edges

The evident and prospective result should be the Common Block between E_1 and E_2 . However, the result of intersection differs.




Figure 75: Result of Intersection

The result contains three new vertices V_{x1} , V_{x2} and V_{x3} , 8 new edges ($V_1, V_{x1}, V_{x2}, V_{x3}, V_2$) and no Common Blocks. This is correct due to the source data: $Tol(E_1)=1.e^{-7}$, $Tol(E_2)=1.e^{-7}$ and $Dmax=1.e^{-6}$.

In this particular case the problem can be solved by several ways:

- Increase, if possible, the values $Tol(E_1)$ and $Tol(E_2)$ to get coincidence in 3D between E_1 and E_2 in terms of tolerance.
- Replace E_1 by a more accurate model.

The example can be extended from 1D (edges) to 2D (faces).




Figure 76: Intersecting Faces

The comments and recommendations are the same as for 1D case above.

14.2.3 Acquired Self-interferences

Example 1: Vertex and edge

Let us consider vertex V_1 and edge E_2 .




Figure 77: Vertex and Edge

Vertex $V1$ interferes with vertices $V12$ and $V22$. So vertex $V21$ should interfere with vertex $V22$, which is impossible because vertices $V21$ and $V22$ are the vertices of edge $E2$, thus $V21$ is not equal to $V22$.

The problem cannot be solved in general, because the length can be as small as possible to provide validity of $E2$ (in the extreme case: $Length(E2) = Tol(V21) + Tol(V22) + e$, where $e \rightarrow 0$).

In a particular case the problem can be solved by refinement of arguments, i.e. by decreasing the values of $Tol(V21)$, $Tol(V22)$ and $Tol(V1)$.

Example 2: Vertex and wire

Let us consider vertex $V2$ and wire consisting of edges $E11$ and $E12$.




Figure 78: Vertex and Wire

The arguments themselves are not self-intersected. Vertex $V2$ interferes with edges $E11$ and $E12$. Thus, edge $E11$ should interfere with edge $E22$, but it is impossible because edges $E11$ and $E12$ cannot interfere by the condition.

The cases when a non-self-interfered argument (or its sub-shapes) become interfered due to the intersections with other arguments (or their sub-shapes) are considered as limitations for the Algorithms.

15 Advanced Options

The previous chapters describe so called Basic Operations. Most of tasks can be solved using Basic Operations. Nonetheless, there are cases that can not be solved straightforwardly by Basic Operations. The tasks are considered as limitations of Basic Operations.

The chapter is devoted to Advanced Options. In some cases the usage of Advanced Options allows overcoming the limitations, improving the quality of the result of operations, robustness and performance of the operators themselves.

15.1 Fuzzy Boolean Operation

Fuzzy Boolean operation is the option of Basic Operations such as General Fuse, Splitting, Boolean, Section, Maker Volume and Cells building operations, in which additional user-specified tolerance is used. This option allows operators to handle robustly cases of touching and near-coincident, misaligned entities of the arguments.

The Fuzzy option is useful on the shapes with gaps or embeddings between the entities of these shapes, which are not covered by the tolerance values of these entities. Such shapes can be the result of modeling mistakes, or translating process, or import from other systems with loss of precision, or errors in some algorithms.

Most likely, the Basic Operations will give unsatisfactory results on such models. The result may contain unexpected and unwanted small entities, faulty entities (in terms of *BRepCheck_Analyzer*), or there can be no result at all.

With the Fuzzy option it is possible to get the expected result – it is just necessary to define the appropriate value of fuzzy tolerance for the operation. To define that value it is necessary to measure the value of the gap (or the value of embedding depth) between the entities of the models, slightly increase it (to make the shifted entities coincident in terms of their tolerance plus the additional one) and pass it to the algorithm.


Fuzzy option is included in interface of Intersection Part (class *BOPAlgo_PaveFiller*) and application programming interface (class *BRepAlgoAPI_BooleanOperation*)

15.1.1 Examples

The following examples demonstrate the advantages of usage Fuzzy option operations over the Basic Operations in typical situations.

Case 1

In this example the cylinder (shown in yellow and transparent) is subtracted from the box (shown in red). The cylinder is shifted by $5e^{-5}$ relatively to the box along its axis (the distance between rear faces of the box and cylinder is $5e^{-5}$).



The following results are obtained using Basic Operations and the Fuzzy ones with the fuzzy value $5e^{-5}$:




Figure 79: Result of CUT operation obtained with Basic Operations





Figure 80: Result of CUT operation obtained with Fuzzy Option

In this example Fuzzy option allows eliminating a very thin part of the result shape produced by Basic algorithm due to misalignment of rear faces of the box and the cylinder.

Case 2

In this example two boxes are fused. One of them has dimensions $10 \times 10 \times 10$, and the other is $10 \times 10.000001 \times 10.000001$ and adjacent to the first one. There is no gap in this case as the surfaces of the neighboring faces coincide, but one box is slightly greater than the other.



The following results are obtained using Basic Operations and the Fuzzy ones with the fuzzy value $1e^{-6}$:




Figure 81: Result of CUT operation obtained with Basic Operations





Figure 82: Result of CUT operation obtained with Fuzzy Option

In this example Fuzzy option allows eliminating an extremely narrow face in the result produced by Basic operation.

Case 3

In this example the small planar face (shown in orange) is subtracted from the big one (shown in yellow). There is a gap $1e^{-5}$ between the edges of these faces.



The following results are obtained using Basic Operations and the Fuzzy ones with the fuzzy value $1e^{-5}$:




Figure 83: Result of CUT operation obtained with Basic Operations





Figure 84: Result of CUT operation obtained with Fuzzy Option

In this example Fuzzy options eliminated a pin-like protrusion resulting from the gap between edges of the argument faces.

Case 4

In this example the small edge is subtracted from the big one. The edges are overlapping not precisely, with max deviation between them equal to $5.28004e^{-5}$. We will use $6e^{-5}$ value for Fuzzy option.



The following results are obtained using Basic Operations and the Fuzzy ones with the fuzzy value $6e^{-5}$:




Figure 85: Result of CUT operation obtained with Basic Operations




Figure 86: Result of CUT operation obtained with Fuzzy Option

This example stresses not only the validity, but also the performance issue. The usage of Fuzzy option with the appropriate value allows processing the case much faster than with the pure Basic operation. The performance gain for the case is 45 (Processor: Intel(R) Core(TM) i5-3450 CPU @ 3.10 GHz).

15.2 Gluing Operation

The Gluing operation is the option of the Basic Operations such as General Fuse, Splitting, Boolean, Section, Maker Volume and Cells building operations. It has been designed to speed up the computation of the interferences among arguments of the operations on special cases, in which the arguments may be overlapping but do not have real intersections between their sub-shapes.

This option cannot be used on the shapes having real intersections, like intersection vertex between edges, or intersection vertex between edge and a face or intersection line between faces:




Figure 87: Intersecting faces

There are two possibilities of overlapping shapes:

- The shapes can be partially coinciding - the faces do not have intersection curves, but overlapping. The faces of such arguments will be split during the operation. The following picture illustrates such shapes:




Figure 88: Partially coinciding faces

- The shapes can be fully coinciding - there should be no partial overlapping of the faces, thus no intersection of type EDGE/FACE at all. In such cases the faces will not be split during the operation.




Figure 89: Full coinciding faces of the boxes

Thus, there are two possible options - for full and partial coincidence of the shapes.

Even though there are no real intersections on such cases without Gluing options the algorithm will still intersect the sub-shapes of the arguments with interfering bounding boxes.

The performance improvement in gluing mode is achieved by excluding the most time consuming computations and in some case can go up to 90%:

- Exclude computation of FACE/FACE intersections for partial coincidence;
- Exclude computation of VERTEX/FACE, EDGE/FACE and FACE/FACE intersections for full coincidence.

By setting the Gluing option for the operation user should guarantee that the arguments are really coinciding. The algorithm does not check this itself. Setting inappropriate option for the operation is likely to lead to incorrect result.

15.2.1 Usage

The Gluing option is an enumeration implemented in `BOPAlgo_GlueEnum.hxx`:

- `BOPAlgo_GlueOff` - default value for the algorithms, Gluing is switched off;
- `BOPAlgo_GlueShift` - Glue option for shapes with partial coincidence;
- `BOPAlgo_GlueFull` - Glue option for shapes with full coincidence.

API level

For setting the Gluing options for the algorithm it is just necessary to call the `SetGlue(const BOPAlgo_Glue)` method with appropriate value:

```
BOPAlgo_Builder aGF;
//
....
// setting the gluing option to speed up intersection of the arguments
aGF.SetGlue(BOPAlgo_GlueShift)
//
....
```

TCL level

For setting the Gluing options in `DRAW` it is necessary to call the `bglue` command with appropriate value:

- 0 - default value, Gluing is off;
- 1 - for partial coincidence;
- 2 - for full coincidence

```
bglue 1
```

15.2.2 Examples

Case1 - Fusing the 64 bspline boxes into one solid




Figure 90: BSpline Boxes with partial coincidence

Performance improvement from using the GlueShift option in this case is about 70 percent.

Case2 - Sewing faces of the shape after reading from IGES




Figure 91: Faces with coinciding but not shared edges

Performance improvement in this case is also about 70 percent.

15.3 Safe processing mode

The safe processing mode is the advanced option in Boolean Operation component. This mode can be applied to all Basic operations such as General Fuse, Splitting, Boolean, Section, Maker Volume, Cells building. This option allows keeping the input arguments untouched. In other words, switching this option on prevents the input arguments from any modification such as tolerance increase, addition of the P-Curves on edges, etc.

The option can be very useful for implementation of the Undo/Redo mechanism in the applications and allows performing the operation many times without changing the inputs.

By default the safe processing option is switched off for the algorithms. Enabling this option might slightly decrease the performance of the operation, because instead of the modification of some entity it will be necessary to create the copy of this entity and modify it. However, this degradation should be very small because the copying is performed only in case of necessity.

The option is also available in the Intersection algorithm - *BOPAlgo_PaveFiller*. To perform several different operations on the same arguments, the safe processing mode can be enabled in *PaveFiller*, prepared only once and then used in operations. It is enough to set this option to *PaveFiller* only and all algorithms taking this *PaveFiller* will also work in the safe mode.

15.3.1 Usage

API level

To enable/disable the safe processing mode for the algorithm, it is necessary to call *SetNonDestructive()* method with the appropriate value:

```
BOPAlgo_Builder aGF;
//
....
// enabling the safe processing mode to prevent modification of the input shapes
aGF.SetNonDestructive(Standard_True);
//
....
```

TCL level

To enable the safe processing mode for the operation in DRAW, it is necessary to call the *bnondestructive* command with the appropriate value:

- 0 - default value, the safe mode is switched off;
- 1 - the safe mode will be switched on.

```
bnondestructive 1
```

15.4 How to disable check of input solids for inverted status

By default, all input solids are checked for inverted status, i.e. the solids are classified to understand if they are holes in the space (negative volumes) or normal solids (positive volumes). The possibility to disable the check of the input solids for inverted status is the advanced option in Boolean Operation component. This option can be applied to all Basic operations, such as General Fuse, Splitting, Boolean, Section, Maker Volume and Cells building. This option allows avoiding time-consuming classification of the input solids and processing them in the same way as positive volumes, saving up to 10 percent of time on the cases with a big number of input solids.

The classification should be disabled only if the user is sure that there are no negative volumes among the input solids, otherwise the result may be invalid.

15.4.1 Usage

API level

To enable/disable the classification of the input solids it is necessary to call *SetCheckInverted()* method with the appropriate value:

```
BOPAlgo_Builder aGF;  
//  
....  
// disabling the classification of the input solid  
aGF.SetCheckInverted(Standard_False);  
//  
....
```

TCL level

To enable/disable the classification of the solids in DRAW, it is necessary to call *bcheckinverted* command with the appropriate value:

- 0 - disabling the classification;
- 1 - default value, enabling the classification.

```
bcheckinverted 0
```

15.5 Usage of Oriented Bounding Boxes

Since Oriented Bounding Boxes are usually much tighter than Axes Aligned Bounding Boxes (for more information on OBB see the Bounding boxes chapter of Modeling data User guide) its usage can significantly speed-up the intersection stage of the operation by reducing the number of interfering objects.

15.5.1 Usage

API level

To enable/disable the usage of OBB in the operation it is necessary to call the *SetUseOBB()* method with the appropriate value:

```
BOPAlgo_Builder aGF;  
//  
....  
// Enabling the usage of OBB in the operation  
aGF.SetUseOBB(Standard_True);  
//  
....
```

TCL level

To enable/disable the usage of OBB in the operation in DRAW it is necessary to call the *buseobb* command with the appropriate value:

- 0 - disabling the usage of OBB;
- 1 - enabling the usage of OBB.

```
buseobb 1
```

16 Errors and warnings reporting system

The chapter describes the Error/Warning reporting system of the algorithms in the Boolean Component.

The errors and warnings are collected in the instance of the class *Message_Report* maintained as a field by common base class of Boolean operation algorithms *BOPAlgo_Options*.

The error is reported in for problems which cannot be treated and cause the algorithm to fail. In this case the result of the operation will be incorrect or incomplete or there will be no result at all.

The warnings are reported for the problems which can be potentially handled or ignored and thus do not cause the algorithms to stop their work (but probably affect the result).

All possible errors and warnings that can be set by the algorithm are listed in its header file. The complete list of errors and warnings that can be generated by Boolean operations is defined in *BOPAlgo_Alerts.hxx*.

Use method *HasErrors()* to check for presence of error; method *HasError()* can be used to check for particular error. Methods *DumpErrors()* outputs textual description of collected errors into the stream. Similar methods *HasWarnings()*, *HasWarning()*, and *DumpWarnings()* are provided for warnings.

Note that messages corresponding to errors and warnings are defined in resource file *BOPAlgo.msg*. These messages can be localized; for that put translated version to separate file and load it in the application by call to *Message_MsgFile::Load()*.

Here is the example of how to use this system:

```
BOPAlgo_PaveFiller aPF;
aPF.SetArguments(...);
aPF.Perform();
if (aPF.HasErrors()) {
    aPF.DumpErrors(std::cerr);
    //
    if (aPF.HasError(STANDARD_TYPE(BOPAlgo_AlertNullInputShapes)) {
        // some actions
    }
    if (aPF.HasWarning(STANDARD_TYPE(BOPAlgo_AlertTooSmallEdge)) {
        // some actions
    }
    ...
}
```

DRAW commands executing Boolean operations output errors and warnings generated by these operations in textual form. Additional option allows saving shapes for which warnings have been generated, as DRAW variables. To activate this option, run command *bdrawwarnshapes* with argument 1 (or with 0 to deactivate):

```
bdrawwarnshapes 1
```

After setting this option and running an algorithm the result will look as follows:

```
Warning: The interfering vertices of the same argument: ws_1_1 ws_1_2
Warning: The positioning of the shapes leads to creation of small edges without valid range: ws_2_1
```

17 History Information

All operations in Boolean Component support History information. This chapter describes how the History is filled for these operations.

Additionally to Vertices, Edges and Faces the history is also available for the Solids.

The rules for filling the History information about Deleted and Modified shapes are the same as for the API algorithms.

Only the rules for Generated shapes require clarification. In terms of the algorithms in Boolean Component the shape from the arguments can have Generated shapes only if these new shapes have been obtained as a result of pure intersection (not overlapping) of this shape with any other shapes from arguments. Thus, the Generated shapes are always:

- VERTICES created from the intersection points and may be Generated from edges and faces only;
- EDGES created from the intersection edges and may be Generated from faces only.

So, only EDGES and FACES could have information about Generated shapes. For all other types of shapes the list of Generated shapes will be empty.

17.1 Examples

Here are some examples illustrating the History information.

17.1.1 Deleted shapes

The result of CUT operation of two overlapping planar faces (see the example below) does not contain any parts from the tool face. Thus, the tool face is considered as Deleted. If the faces are not fully coinciding, the result must contain some parts of the object face. In this case object face will be considered as not deleted. But if the faces are fully coinciding, the result must be empty, and both faces will be considered as Deleted.

Example of the overlapping faces:

```
plane p 0 0 0 0 0 1
mkface f1 p -10 10 -10 10
mkface f2 p 0 20 -10 10

bclearobjects
bcleartools
baddobjects f1
baddtools f2
bfillds
bbop r 2

savehistory cut_hist
isdeleted cut_hist f1
# Not deleted

isdeleted cut_hist f2
# Deleted
```

17.1.2 Modified shapes

In the FUSE operation of two edges intersecting in one point (see the example below), both edges will be split by the intersection point. All these splits will be contained in the result. Thus, each of the input edges will be Modified into its two splits. But in the CUT operation on the same edges, the tool edge will be Deleted from the result and, thus, will not have any Modified shapes.

Example of the intersecting edges:

```
line l1 0 0 0 1 0 0
mkedge e1 l1 -10 10
```

```

line l2 0 0 0 0 1 0
mkedge e2 l2 -10 10

bclearobjects
bcleartools
baddobjects e1
baddtools e2
bfilllds

# fuse operation
bbop r 1

savehistory fuse_hist

modified m1 fuse_hist e1
nbshapes m1
# EDGES: 2

modified m2 fuse_hist e2
nbshapes m2
# EDGES: 2

# cut operation
bbop r 2

savehistory cut_hist

modified m1 cut_hist e1
nbshapes m1
# EDGES: 2

modified m2 cut_hist e2
# The shape has not been modified

```

17.1.3 Generated shapes

Two intersecting edges will both have the intersection vertices Generated from them.

As for the operation with intersecting faces, consider the following example:

```

plane p1 0 0 0 0 0 1
mkface f1 p1 -10 10 -10 10

plane p2 0 0 0 1 0 0
mkface f2 p2 -10 10 -10 10

bclearobjects
bcleartools
baddobjects f1
baddtools f2
bfilllds

# fuse operation
bbop r 1

savehistory fuse_hist

generated gf1 fuse_hist f1
nbshapes gf1
# EDGES: 1

generated gf2 fuse_hist f2
nbshapes gf2
# EDGES: 1

# common operation - result is empty
bbop r 0

savehistory com_hist

generated gf1 com_hist f1
# No shapes were generated from the shape

generated gf2 com_hist f2
# No shapes were generated from the shape

```

18 Usage

The chapter contains some examples of the OCCT Boolean Component usage. The usage is possible on two levels: C++ and Tcl.

18.1 Package BRepAlgoAPI

The package *BRepAlgoAPI* provides the Application Programming Interface of the Boolean Component.

The package consists of the following classes:

- *BRepAlgoAPI_Algo* – the root class that provides the interface for algorithms.
- *BRepAlgoAPI_BuilderAlgo* – the class API level of General Fuse algorithm.
- *BRepAlgoAPI_Splitter* – the class API level of the Splitter algorithm.
- *BRepAlgoAPI_BooleanOperation* – the root class for the classes *BRepAlgoAPI_Fuse*, *BRepAlgoAPI_Common*, *BRepAlgoAPI_Cut* and *BRepAlgoAPI_Section*.
- *BRepAlgoAPI_Fuse* – the class provides Boolean fusion operation.
- *BRepAlgoAPI_Common* – the class provides Boolean common operation.
- *BRepAlgoAPI_Cut* – the class provides Boolean cut operation.
- *BRepAlgoAPI_Section* – the class provides Boolean section operation.




Figure 92: Diagram of BRepAlgoAPI package

The detailed description of the classes can be found in the corresponding .hxx files. The examples are below in this chapter.

18.2 Package BOPTest

The package *BOPTest* provides the usage of the Boolean Component on Tcl level. The method *BOPTest::API* contains corresponding Tcl commands:

- *bapibuild* – for General Fuse Operator;
- *bapisplit* – for Splitter Operator;
- *bapibop* – for Boolean Operator and Section Operator.

The examples of how to use the commands are below in this chapter.

18.2.1 Case 1. General Fuse operation

The following example illustrates how to use General Fuse operator:

C++ Level

```
#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include <BRepAlgoAPI_BuilderAlgo.hxx>
{...
  BRepAlgoAPI_BuilderAlgo aBuilder;
  //
  // prepare the arguments
  TopTools_ListOfShape& aLS=...;
  //
  // set the arguments
  aBuilder.SetArguments(aLS);

  // Set options for the algorithm
  // setting options on this level is similar to setting options to GF algorithm on low level (see "GF
  Usage" chapter)
  ...

  // run the algorithm
  aBuilder.Build();
  if (aBuilder.HasErrors()) {
    // an error treatment
    return;
  }
  //
  // result of the operation aR
  const TopoDS_Shape& aR=aBuilder.Shape();
  ...
}
```

Tcl Level

```
# prepare the arguments
box b1 10 10 10
box b2 3 4 5 10 10 10
box b3 5 6 7 10 10 10
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the arguments
baddobjects b1 b2 b3

# set options for the algorithm (see "GF Usage" chapter)
...

# run the algorithm
# r is the result of the operation
bapibuild r
```

18.2.2 Case 2. Splitting operation

The following example illustrates how to use the Splitter operator:

C++ Level

```

#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include <BRepAlgoAPI_Splitter.hxx>
//
BRepAlgoAPI_BuilderAlgo aSplitter;
//
// prepare the arguments
// objects
TopTools_ListOfShape& aLSObjects = ... ;
// tools
TopTools_ListOfShape& aLSTools = ... ;
//
// set the arguments
aSplitter.SetArguments(aLSObjects);
aSplitter.SetTools(aLSTools);
//
// Set options for the algorithm
// setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
// chapter)
...
//
// run the algorithm
aSplitter.Build();
// check error status
if (aSplitter.HasErrors()) {
    return;
}
//
// result of the operation aResult
const TopoDS_Shape& aResult = aSplitter.Shape();

```

Tcl Level

```

# prepare the arguments
# objects
box b1 10 10 10
box b2 7 0 0 10 10 10

# tools
plane p 10 5 5 0 1 0
mkface f p -20 20 -20 20
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the objects
baddobjects b1 b2
# set the tools
baddtools f
#
# set options for the algorithm (see "GF Usage" chapter)
...
#
# run the algorithm
# r is the result of the operation
bapisplit r

```

18.2.3 Case 3. Common operation

The following example illustrates how to use Common operation:

C++ Level

```

#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include <BRepAlgoAPI_Common.hxx>
{...
    Standard_Boolean bRunParallel;
    Standard_Real aFuzzyValue;
    BRepAlgoAPI_Common aBuilder;

    // prepare the arguments
    TopTools_ListOfShape& aLS=...;
    TopTools_ListOfShape& aLT=...;
    //
    bRunParallel=Standard_True;
    aFuzzyValue=2.1e-5;
    //
    // set the arguments

```

```

aBuilder.SetArguments(aLS);
aBuilder.SetTools(aLT);
//
// Set options for the algorithm
// setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
// chapter)
...
//
// run the algorithm
aBuilder.Build();
if (aBuilder.HasErrors()) {
    // an error treatment
    return;
}
//
// result of the operation aR
const TopoDS_Shape& aR=aBuilder.Shape();
...
}

```

Tcl Level

```

# prepare the arguments
box b1 10 10 10
box b2 7 0 4 10 10 10
box b3 14 0 0 10 10 10
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the arguments
baddobjects b1 b3
baddtools b2
#
# set options for the algorithm (see "GF Usage" chapter)
...
#
# run the algorithm
# r is the result of the operation
# 0 means Common operation
bapibop r 0

```

18.2.4 Case 4. Fuse operation

The following example illustrates how to use Fuse operation:

C++ Level

```

#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include < BRepAlgoAPI_Fuse.hxx>
{...
    Standard_Boolean bRunParallel;
    Standard_Real aFuzzyValue;
    BRepAlgoAPI_Fuse aBuilder;

    // perpare the arguments
    TopTools_ListOfShape& aLS=...;
    TopTools_ListOfShape& aLT=...;
    //
    bRunParallel=Standard_True;
    aFuzzyValue=2.1e-5;
    //
    // set the arguments
    aBuilder.SetArguments(aLS);
    aBuilder.SetTools(aLT);
    //
    // Set options for the algorithm
    // setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
    // chapter)
    ...
    //
    // run the algorithm
    aBuilder.Build();
    if (aBuilder.HasErrors()) {
        // an error treatment
        return;
    }
    //
    // result of the operation aR
    const TopoDS_Shape& aR=aBuilder.Shape();
}

```

```
...
}
```

Tcl Level

```
# prepare the arguments
box b1 10 10 10
box b2 7 0 4 10 10 10
box b3 14 0 0 10 10 10
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the arguments
baddobjects b1 b3
baddtools b2
#
# set options for the algorithm (see "GF Usage" chapter)
...
#
# run the algorithm
# r is the result of the operation
# 1 means Fuse operation
bapibop r 1
```

18.2.5 Case 5. Cut operation

The following example illustrates how to use Cut operation:

C++ Level

```
#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include < BRepAlgoAPI_Cut.hxx>
{...
  Standard_Boolean bRunParallel;
  Standard_Real aFuzzyValue;
  BRepAlgoAPI_Cut aBuilder;

  // perpare the arguments
  TopTools_ListOfShape& aLS=...;
  TopTools_ListOfShape& aLT=...;
  //
  bRunParallel=Standard_True;
  aFuzzyValue=2.1e-5;
  //
  // set the arguments
  aBuilder.SetArguments(aLS);
  aBuilder.SetTools(aLT);
  //
  // Set options for the algorithm
  // setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
  chapter)
  ...
  //
  // run the algorithm
  aBuilder.Build();
  if (aBuilder.HasErrors()) {
    // an error treatment
    return;
  }
  //
  // result of the operation aR
  const TopoDS_Shape& aR=aBuilder.Shape();
  ...
}
```

Tcl Level

```
# prepare the arguments
box b1 10 10 10
box b2 7 0 4 10 10 10
box b3 14 0 0 10 10 10
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the arguments
baddobjects b1 b3
baddtools b2
```

```

#
# set options for the algorithm (see "GF Usage" chapter)
...
#
# run the algorithm
# r is the result of the operation
# 2 means Cut operation
bapibop r 2

```

18.2.6 Case 6. Section operation

The following example illustrates how to use Section operation:

C++ Level

```

#include <TopoDS_Shape.hxx>
#include <TopTools_ListOfShape.hxx>
#include < BRepAlgoAPI_Section.hxx>
{...
  Standard_Boolean bRunParallel;
  Standard_Real aFuzzyValue;
  BRepAlgoAPI_Section aBuilder;

  // prepare the arguments
  TopTools_ListOfShape& aLS=...;
  TopTools_ListOfShape& aLT=...;
  //
  bRunParallel=Standard_True;
  aFuzzyValue=2.1e-5;
  //
  // set the arguments
  aBuilder.SetArguments(aLS);
  aBuilder.SetTools(aLT);
  //
  // Set options for the algorithm
  // setting options for this algorithm is similar to setting options for GF algorithm (see "GF Usage"
  chapter)
  ...
  //
  // run the algorithm
  aBuilder.Build();
  if (aBuilder.HasErrors()) {
    // an error treatment
    return;
  }
  //
  // result of the operation aR
  const TopoDS_Shape& aR=aBuilder.Shape();
  ...
}

```

Tcl Level

```

# prepare the arguments
box b1 10 10 10
box b2 3 4 5 10 10 10
box b3 5 6 7 10 10 10
#
# clear inner contents
bclearobjects; bcleartools;
#
# set the arguments
baddobjects b1 b3
baddtools b2
#
# set options for the algorithm (see "GF Usage" chapter)
...
#
# run the algorithm
# r is the result of the operation
# 4 means Section operation
bapibop r 4

```